

Mercusys MS105GS - Desktop switch, 5 Gigabit ports, black

Gamintojas: **MERCUSYS** · Modelis: **MS105GS** · EAN: **6957939001315** · Prekės kodas: **539376**



15,90 €

Kaina su PVM

Be PVM: 13,14 €

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt



Aprašymas

Certification: CE, RoHS | Width: 99.8 mm | Rack mounting: No | Packet buffer memory: 0.125 MB | Power supply included: Yes | MAC address auto-aging supported: Yes | Power source: DC | MAC address auto-learning supported: Yes | Stackable: No | Basic switching RJ-45 Ethernet ports quantity: 5 | Depth: 98 mm | Power consumption (max): 3.614 W | Heat dissipation: 12.331 BTU/h | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Auto-negotiation: Yes | Power connector: DC-in jack | Switching capacity: 10 Gbit/s | Switch type: Unmanaged | Height: 25.1 mm | Full duplex: Yes | Flow control support: Yes | Product colour: Black | Half duplex: Yes | Jumbo frames: 9000 | Auto MDI/MDI-X: Yes | Wall mountable: Yes | Store-and-forward: Yes | MAC address table: 2000 entries | Cables included: AC | DC input voltage: 5 V | Jumbo frames support: Yes | Housing material: Metal | Fanless: Yes | Transmission distance (max): 0.1 km | 10G support: No | AC input frequency: 50/60 Hz | LED indicators: Yes | Storage temperature (T-T): -40 - 70 °C | AC input voltage: 220 V | Power over Ethernet (PoE): No | Quick start guide: Yes | Operating temperature (T-T): 0 - 40 °C | Operating relative humidity (H-H): 10 - 90% | Input current: 0.6 A | Networking standards: IEEE 802.3p | Networking standards: IEEE 802.3x | Networking standards: IEEE 802.3u | Storage relative humidity (H-H): 5 - 95% | Networking standards: IEEE 802.3 | Networking standards: IEEE 802.3ab

Techninė specifikacija

Specifications	
Sandėlio grupė	Switches [+83][-71]
Matmenys ir svoris	

Matmenys (l × P × A)	10,00cm × 13,00cm × 13,00cm
Svoris	0,30kg