



**TP-Link Omada
SG5428X
network switch
Managed L3
Gigabit Ethernet
(10/100/1000)
Black**

Modelis: SG5428X

Gamintojas: TP-LINK

EAN: 8885020626421

Prekės kodas: 539377

414.99€

Networking standards: IEEE 802.3at | Operating relative humidity (H-H): 10 - 90% | Security algorithms: SNMPv2 | Power consumption (max): 19.6 W | Product colour: Black | Networking standards: IEEE 802.3af | Quick start guide: Yes | Processor frequency: 1200 MHz | Web-based management: Yes | MAC address filtering: Yes | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | Power over Ethernet (PoE): No | Security algorithms: SNMP | USB 2.0 ports quantity: 1 | AC input frequency: 50/60 Hz | Firmware upgradeable: Yes | Security algorithms: SNMPv3 | Operating temperature (T-T): -5 - 45 °C | AC input voltage: 100 - 240 V | Networking standards: IEEE 802.3bt | Storage relative humidity (H-H): 5 - 90% | LED indicators: Yes | Compliance certificates: Federal Communications Commission (FCC) | Compliance certificates: RoHS | _____

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

Compliance certificates: CE | Switch type: Managed | Processor manufacturer: ARM | Gigabit Ethernet (copper) ports quantity: 24 | VLAN support: Yes | Jumbo frames: 9000 | Surge protection: Yes | Broadcast storm control: Yes | Basic switching RJ-45 Ethernet ports quantity: 24 | Flash memory: 512 MB | IP-MAC-Port binding: Yes | Password protection: Yes | Store-and-forward: Yes | Link aggregation: Yes | Bandwidth: 64 Gbit/s | Fanless: Yes | Virtual LAN features: MAC address-based VLAN | Virtual LAN features: Protocol-based VLAN | Multicast support: Yes | Virtual LAN features: Voice VLAN | Jumbo frames support: Yes | Virtual LAN features: Private VLAN | Built-in processor: Yes | Stackable: Yes | Management level: 4 | DHCP features: DHCP relay | Switching capacity: 128 Gbit/s | Depth: 180 mm | USB Type-C ports quantity: 1 | Switch layer: L3 | Forwarding rate: 95.23 Mpps | Power supply included: Yes | Rack mounting: Yes | Internal memory: 2000 MB | SSH/SSL support: Yes | ARP inspection: Yes | Width: 440 mm | 10G support: Yes | Number of VLANs: 4000 | Rack mount kit: Yes | IGMP snooping: Yes | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Mean time between failures (MTBF): 519.543 h | Heat dissipation: 66.87 BTU/h | Power source: AC | Packet buffer memory: 12 MB | Console port: RJ-45 | SFP+ module slots quantity: 4 | Access Control List (ACL): Yes | DHCP features: DHCP server | Port mirroring: Yes | MAC address table: 16000 entries | Height: 44 mm | Cables included: AC | Surge protection voltage: 6 kV | Physical stacking (units): 4 | Static port security: Yes | Cloud-managed: Yes | Telnet: Yes | Memory type: DRAM