



TP-Link 24-Port 10/100Mbps + 2- Port Gigabit Unmanaged PoE+ Switch



Modelis: TL-SL1226P

Gamintojas: TP-LINK

EAN: 6935364089443

Prekės kodas: 539402

144.99€

Certification: CE, FCC, RoHS | Combo SFP ports quantity: 2 | Jumbo frames: 10000 | Gigabit Ethernet (copper) ports quantity: 2 | Forwarding rate: 6.54 Mpps | Fast Ethernet (copper) ports quantity: 24 | Store-and-forward: Yes | Rack mount kit: Yes | Auto-negotiation: Yes | Traffic classification: Yes | Power over Ethernet plus (PoE+) ports quantity: 24 | Warnings: Ensure the unit is adequately ventilated during operation. | Warnings: The product is not suitable for disposal in the regular waste bin. Take your used electronic equipment to a recycling centre in accordance with local regulations. | Warnings: Do not open the case or try to repair it yourself. | Form factor: 1U | LED indicators: Yes | Operating relative humidity (H-H): 10 - 90% | AC input voltage: 100 - 240 V | Product colour: Grey | Storage temperature (T-T): -40 - 70 °C | Operating temperature (T-T): 0 - 50 °C | Quick start guide: Yes | Package weight: 3.02 kg | Power over Ethernet (PoE): Yes | Networking standards: IEEE 802.3af | Networking standards: IEEE 802.3x | Networking standards: IEEE 802.3at | 10G support: No | Basic switching RJ-45 Ethernet ports quantity: 26 | Package height: 80 mm | Package depth: 528 mm |

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

Power supply included: Yes | Copper ethernet cabling technology: 10BASE-T | Copper ethernet cabling technology: 100BASE-TX | Number of fans: 2 fan(s) | Package width: 250 mm | Height: 44 mm | Heat dissipation: 1002.54 BTU/h | Packet buffer memory: 4.1 MB | Auto MDI/MDI-X: Yes | MAC address table: 8000 entries | Copper ethernet cabling technology: 1000BASE-T | Total Power over Ethernet (PoE) budget: 250 W | Power source: AC | Jumbo frames support: Yes | Switch type: Unmanaged | Power consumption (max): 281 W | Power over Ethernet (PoE) power per port: 30 W | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Storage relative humidity (H-H): 5 - 90% | Switching capacity: 8.8 Gbit/s | Harmonized System (HS) code: 85176990 | Depth: 180 mm | Rack mounting: Yes | Width: 440 mm