



**Optoma
HZ146X-W
Standard throw
projector 3800
ANSI lumens
DLP 1080p
(1920x1080) 3D
White**

Modelis: E9PD7KK01EZ1E

Gamintojas: OPTOMA

EAN: 5055387668201

Prekės kodas: 539601

659.99€

Analog signal format system: NTSC M | Analog signal format system: PAL M | Analog signal format system: PAL H | Analog signal format system: PAL N | Supported video modes: 576i | Analog signal format system: PAL B | Analog signal format system: PAL G | Analog signal format system: PAL 4.43 | USB 2.0 ports quantity: 1 | Power consumption (typical): 88 W | Analog signal format system: SECAM K | Analog signal format system: SECAM G | Analog signal format system: SECAM 4.25/4.4 | International Protection (IP) code: IP6X | Operating temperature (T-T): 0 - 40 °C | Supported video modes: 480p | Supported video modes: 1080p | Batteries included: Yes | Supported video modes: 1080i | Horizontal scan range: 15 - 140 kHz | Power source: AC | Analog signal format system: PAL I |

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

Analog signal format system: SECAM K1 | Analog signal format system: NTSC 3.58 | Analog signal format system: SECAM L | Native aspect ratio: 16:9 | Analog signal format system: PAL D | Analog signal format system: SECAM B | Supported video modes: 720p | Manual: Yes | Analog signal format system: NTSC 4.43 | Operating relative humidity (H-H): 0 - 80% | Supported video modes: 576p | Full HD: Yes | Depth: 216 mm | Package weight: 4.2 kg | Supported video modes: 480i | Cable lock slot type: Kensington | Analog signal format system: SECAM D | Analog signal format system: NTSC J | DVI port: No | Package width: 310 mm | HDMI ports quantity: 2 | Width: 274 mm | Weight: 3 kg | Product colour: White | Product type: Standard throw projector | Cables included: Power | Height: 114 mm | Power consumption (max): 139 W | Package depth: 250 mm | Noise level: 34 dB | HDMI version: 2.0 | 3D: Yes | Cable lock slot: Yes | On Screen Display (OSD): Yes | Built-in speaker(s): Yes | Serial interface type: RS-232 | Vertical scan range: 24 - 120 Hz | RMS rated power: 15 W | Package height: 120 mm | Remote control included: Yes | Supported aspect ratios: 4:3 | Contrast ratio (typical): 2000000:1 | Audio (L/R) in: 1 | Power consumption (standby): 0.5 W | Focal length range: 12.81 - 16.74 mm | Commodity code: 8528620000 | Offset: 116% | Supported aspect ratios: 16:10 | Supported aspect ratios: 16:9 | Keystone correction, vertical: +\ -30° | Zoom type: Manual | Throw ratio: 1.48:1 - 1.62:1 | HDMI connector type: Full-size | Supported 3D formats: Frame Sequential | Projector brightness: 3800 ANSI lumens | Service life of light source: 30000 h | Projector native resolution: 1080p (1920x1080) | Screen size compatibility: 508 - 7620 mm (20 - 300") | Projection distance: 0.8 - 10 m | Uniformity: 75% | Number of colours: 1.073 billion colours | Light source type: Laser | Zoom ratio: 1.1:1 | Projection technology: DLP | Keystone correction, horizontal: +\ -30°