



TP-Link Omada AX5400 Multi- Gigabit Ceiling Mount WiFi 6 Access Point



Modelis: EAP770

Gamintojas: TP-LINK

EAN: 1210002608718

Prekės kodas: 539711

204.99€

Certification: CE, FCC, RoHS | Maximum data transfer rate (2.4 GHz): 688 Mbit/s | Automatic channel selection: Yes | DC voltage range: 12 V | Maximum data transfer rate (5 GHz): 2882 Mbit/s | Access Control List (ACL): Yes | Width: 220 mm | Maximum data transfer rate (6 GHz): 5765 Mbit/s | MIMO type: Multi User MIMO | Flow control support: Yes | Rate limiting: Yes | Airtime Fairness (ATF): Yes | Height: 32.5 mm | Depth: 220 mm | 6 GHz: Yes | Band steering: Yes | Transmitting power (CE): 20 dBm (2.4 GHz, EIRP) 23 dBm (5 GHz, band 1&band 2, EIRP) 28 dBm (5 GHz, band 3, EIRP) 23dBm (6 GHz, EIRP) | VLAN support: Yes | BeamForming: Yes | Automatic channel scanning: Yes | Syslog: Yes | Cabling technology: 10/100/1000/2500Base-T | Fit AP mode features: Mesh networking | Transmitting power (FCC): 25 dBm (2.4 GHz) 25 dBm (5 GHz) 23 dBm (6 GHz | Operating temperature (T-T): 0 - 40 °C | Operating relative humidity (H-H): 10 - 90% | Product colour: White | MIMO: Yes | Spread spectrum method: OFDMA | Quick start guide: Yes | Quantity per pack: 1 pc(s) | Ethernet LAN data rates: 2500 Mbit/s | Firmware upgradeable: Yes | Ethernet LAN data rates: 10 |

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

Weight: 730 g | DC-in jack: Yes | Antenna type: Internal | 5 GHz: Yes | LED indicators: Yes |
Networking standards: IEEE 802.11ac | Security algorithms: SNMPv3 | Security algorithms: WPA-
Personal | Storage relative humidity (H-H): 5 - 90% | Reset button: Yes | Web-based management:
Yes | 2.4 GHz: Yes | Ethernet LAN data rates: 100 Mbit/s | Storage temperature (T-T): -40 - 70 °C |
Quality of Service (QoS) support: Yes | Package type: Box | Input current: 2.5 A | Ethernet LAN (RJ-45)
ports: 1 | Networking standards: IEEE 802.11be | Security algorithms: WPA2-Enterprise | Security
algorithms: SNMPv2 | Networking standards: IEEE 802.11ax | Placement: Ceiling, Wall | Ethernet LAN
data rates: 1000 | Mounting kit: Yes | Security algorithms: SNMP | Security algorithms: WPA3-
Enterprise | Networking standards: IEEE 802.11g | Networking standards: IEEE 802.11n | Security
algorithms: WPA-Enterprise | Security algorithms: WPA2-Personal | MAC address filtering: Yes |
Networking standards: IEEE 802.11a | Power over Ethernet (PoE): Yes | Networking standards: IEEE
802.11b