

TP-Link Omada AX5400 Multi-Gigabit Ceiling Mount WiFi 6 Access Point

Gamintojas: **TP-LINK** · Modelis: **EAP770** · EAN: **1210002608718** · Prekės kodas: **539711**



199,90 €

Kaina su PVM

Be PVM: **165,21 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt



Aprašymas

Certification: CE, FCC, RoHS | Rate limiting: Yes | Band steering: Yes | Maximum data transfer rate (2.4 GHz): 688 Mbit/s | Maximum data transfer rate (6 GHz): 5765 Mbit/s | Depth: 220 mm | Transmitting power (CE): 20 dBm (2.4 GHz, EIRP) 23 dBm (5 GHz, band 1&band 2, EIRP) 28 dBm (5 GHz, band 3, EIRP) 23dBm (6 GHz, EIRP) | Automatic channel selection: Yes | DC voltage range: 12 V | Maximum data transfer rate (5 GHz): 2882 Mbit/s | Fit AP mode features: Mesh networking | Airtime Fairness (ATF): Yes | Automatic channel scanning: Yes | Width: 220 mm | 6 GHz: Yes | Height: 32.5 mm | Flow control support: Yes | MIMO type: Multi User MIMO | Syslog: Yes | BeamForming: Yes | Transmitting power (FCC): 25 dBm (2.4 GHz) 25 dBm (5 GHz) 23 dBm (6 GHz | Access Control List (ACL): Yes | VLAN support: Yes | Cabling technology: 10/100/1000/2500Base-T | 5 GHz: Yes | Antenna type: Internal | MIMO: Yes | Web-based management: Yes | MAC address filtering: Yes | 2.4 GHz: Yes | Product colour: White | DC-in jack: Yes | Firmware upgradeable: Yes | Operating temperature (T-T): 0 - 40 °C | Ethernet LAN (RJ-45) ports: 1 | LED indicators: Yes | Networking standards: IEEE 802.11g | Networking standards: IEEE 802.11n | Quantity per pack: 1 pc(s) | Networking standards: IEEE 802.11a | Ethernet LAN data rates: 2500 | Power over Ethernet (PoE): Yes | Placement: Ceiling, Wall | Networking standards: IEEE 802.11ax | Weight: 730 g | Ethernet LAN data rates: 100 Mbit/s | Security algorithms: WPA-Enterprise | Networking standards: IEEE 802.11be | Security algorithms: WPA2-Enterprise | Security algorithms: SNMPv2 | Reset button: Yes | Ethernet LAN data rates: 1000 | Quick start guide: Yes | Mounting kit: Yes | Spread spectrum method: OFDMA | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | Input current: 2.5 A | Operating relative humidity (H-H): 10 - 90% | Security algorithms: SNMP | Security algorithms: WPA-Personal | Storage relative humidity (H-H): 5 - 90% | Security algorithms: WPA3-Enterprise | Networking standards: IEEE 802.11b | Security algorithms: WPA2-Personal | Networking standards: IEEE 802.11ac | Ethernet LAN data rates: 10 | Package type: Box | Security algorithms: SNMPv3

Techninė specifikacija

Specifications

Sandėlio grupė	AccesPoint [+37][-28]
----------------	-----------------------

Matmenys ir svoris

Matmenys (I × P × A)	9,00cm × 28,00cm × 26,00cm
----------------------	----------------------------

Svoris	1,40kg
--------	--------