



OMADA ES220GP network switch Managed Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) Black

Modelis: ES220GP

Gamintojas: TP-LINK

EAN: 1210002609746

Prekės kodas: 539823

190.99€

Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | MAC address table: 8000 entries | Rack mounting: Yes | Power source: AC | Jumbo frames support: Yes | Auto MDI/MDI-X: Yes | Packet buffer memory: 4 MB | Width: 294 mm | Power over Ethernet (PoE): Yes | Switching capacity: 40 Gbit/s | Power consumption (max): 182.43 W | Power connector: AC-in jack | Cables included: AC | Ethernet LAN data rates: 10,100,1000 Mbit/s | Height: 44 mm | Operating temperature (T-T): -5 - 40 °C | AC input voltage: 100 - 240 V | Depth: 180 mm | User guide: Yes | Number of

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

VLANs: 32 | Product colour: Black | SFP module slots quantity: 2 | Noise level: 20.1 dB | AC input frequency: 50/60 Hz | Input current: 2.5 A | Multicast support: Yes | Operating relative humidity (H-H): 10 - 90% | Mean time between failures (MTBF): 320156 h | 10G support: No | DHCP features: DHCP client | VLAN support: Yes | IGMP snooping: Yes | Total Power over Ethernet (PoE) budget: 150 W | Basic switching RJ-45 Ethernet ports quantity: 18 | Networking standards: IEEE 802.1Q | Networking standards: IEEE 802.3x | Networking standards: IEEE 802.3at | Storage relative humidity (H-H): 5 - 90% | Networking standards: IEEE 802.1ab | Power over Ethernet (PoE) power per port: 30 W | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Networking standards: IEEE 802.3af | Web-based management: Yes | Networking standards: IEEE 802.1p | Housing material: Metal | Virtual LAN features: Tagged VLAN | Virtual LAN features: Port-based VLAN | Forwarding rate: 29.76 Mpps | Virtual LAN features: MTU VLAN | Port mirroring: Yes | Link aggregation: Yes | Cloud-managed: Yes | Broadcast storm control: Yes | Gigabit Ethernet (copper) ports quantity: 18 | Auto-negotiation: Yes | Power over Ethernet (PoE) type supported: PoE+ | Fanless: Yes | Switch type: Managed | Number of queues: 8 | Power over Ethernet plus (PoE+) ports quantity: 16 | Store-and-forward: Yes | Flow control support: Yes | Queue scheduling algorithms: Weighted Round Robin (WRR) | Compliance certificates: Federal Communications Commission (FCC) | Compliance certificates: RoHS | Compliance certificates: CE