



Zyxel GS1200-8V3 Managed L2 Gigabit Ethernet (10/100/1000) Desktop Grey



Modelis: GS1200-8V3-EU0101F

Gamintojas: ZYXEL

EAN: 4718937649945

Prekės kodas: 539830

30.00€

Certification: CE-LVD, BSMI CE, EAC, FCC, BSMI Class B | AC input voltage: 100 - 240 V | AC input frequency: 50/60 Hz | Product colour: Grey | Networking standards: IEEE 802.1Q | Networking standards: IEEE 802.3x | Networking standards: IEEE 802.3ad | Web-based management: Yes | Networking standards: IEEE 802.3 | Networking standards: IEEE 802.3ab | Networking standards: IEEE 802.1p | Networking standards: IEEE 802.3u | Networking standards: IEEE 802.3az | Storage relative humidity (H-H): 10 - 95% | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Width: 193 mm | DHCP features: DHCP client | Copper ethernet cabling technology: 10BASE-T | Copper ethernet cabling technology: 100BASE-T | Jumbo frames: 15 | Broadcast storm control: Yes | MAC address table: 4000 entries | Basic switching RJ-45 Ethernet ports quantity: 8 | Password protection: Yes | Jumbo frames support: Yes | Rack mounting: No | Power over Ethernet (PoE): No | Full duplex: Yes | Virtual LAN features: Port-based VLAN | Height: 26 mm | IGMP snooping: Yes | Stackable: No | Heat dissipation: 13 BTU/h | Weight: 268 g | Power source: AC | VLAN support:

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

Yes | Number of multicast groups filtered: 128 | Power connector: DC-in jack | Port mirroring: Yes | Operating relative humidity (H-H): 10 - 95% | Power supply included: Yes | Depth: 85 mm | Multicast support: Yes | Switch layer: L2 | LED indicators: Yes | Mean time between failures (MTBF): 1266805 h | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | Packet buffer memory: 0.192 MB | Flow control support: Yes | Queue scheduling algorithms: Weighted Round Robin (WRR) | Power consumption (max): 3.81 W | Forwarding rate: 11.9 Mpps | Copper ethernet cabling technology: 1000BASE-T | 10G support: No | Switch type: Managed | Operating temperature (T-T): 0 - 50 °C | Fanless: Yes | Form factor: Desktop | Switching capacity: 16 Gbit/s