



Zyxel GS1200-5HPV3 Managed L2 Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) Desktop Grey



Modelis: GS1200-5HPV3-EU0101F

Gamintojas: ZYXEL

EAN: 4718937649815

Prekės kodas: 539831

54.99€

Certification: CE-LVD, BSMI CE, EAC, FCC, BSMI Class B | Power over Ethernet (PoE): Yes | Port mirroring: Yes | Form factor: Desktop | DHCP features: DHCP client | Rack mounting: No | Operating relative humidity (H-H): 10 - 95% | Power supply included: Yes | Depth: 85 mm | Multicast support: Yes | Stackable: No | Packet buffer memory: 0.192 MB | Power source: AC/PoE | MAC address table: 4000 entries | Width: 155 mm | IGMP snooping: Yes | Operating temperature (T-T): 0 - 50 °C | Fanless: Yes | Power over Ethernet (PoE) ports quantity: 4 | Power consumption (max): 4.153 W | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | Flow control support: Yes | Mean time between failures (MTBF): 1730334 h | Heat dissipation: 44.788 BTU/h | Virtual LAN

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

features: Port-based VLAN | Forwarding rate: 7.44 Mpps | Power connector: DC-in jack | Broadcast storm control: Yes | Switch layer: L2 | Jumbo frames: 15 | Total Power over Ethernet (PoE) budget: 68 W | Weight: 274 g | Switching capacity: 10 Gbit/s | 10G support: No | Switch type: Managed | Height: 26 mm | Jumbo frames support: Yes | Password protection: Yes | Storage relative humidity (H-H): 10 - 95% | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Full duplex: Yes | Queue scheduling algorithms: Weighted Round Robin (WRR) | Copper ethernet cabling technology: 10BASE-T | Copper ethernet cabling technology: 100BASE-T | VLAN support: Yes | Number of multicast groups filtered: 128 | Basic switching RJ-45 Ethernet ports quantity: 5 | Copper ethernet cabling technology: 1000BASE-T | AC input voltage: 100 - 240 V | LED indicators: Yes | Product colour: Grey | AC input frequency: 50/60 Hz | Networking standards: IEEE 802.1Q | Networking standards: IEEE 802.3x | Networking standards: IEEE 802.3u | Networking standards: IEEE 802.3at | Web-based management: Yes | Networking standards: IEEE 802.3 | Networking standards: IEEE 802.3ab | Networking standards: IEEE 802.1p | Networking standards: IEEE 802.3ad | Networking standards: IEEE 802.3az