



Zyxel GS1200-8HPV3 Managed L2 Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) Desktop Grey



Modelis: GS1200-8HPV3-EU0101F

Gamintojas: ZYXEL

EAN: 4718937649907

Prekės kodas: 539832

58.99€

Certification: CE-LVD, BSMI CE, EAC, FCC, BSMI Class B | Stackable: No | Virtual LAN features: Port-based VLAN | Jumbo frames: 15 | Forwarding rate: 11.9 Mpps | Fanless: Yes | Queue scheduling algorithms: Weighted Round Robin (WRR) | Broadcast storm control: Yes | Number of multicast groups filtered: 128 | Copper ethernet cabling technology: 10BASE-T | Copper ethernet cabling technology: 100BASE-T | Power over Ethernet (PoE) ports quantity: 4 | AC input frequency: 50/60 Hz | DHCP features: DHCP client | VLAN support: Yes | Password protection: Yes | Form factor: Desktop | Port mirroring: Yes | Height: 26 mm | Switch layer: L2 | Packet buffer memory: 0.192 MB | Power consumption (max): 81.27 W | MAC address table: 4000 entries | Power source: AC/PoE | Operating

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

temperature (T-T): 0 - 50 °C | Rack mounting: No | Full duplex: Yes | Mean time between failures (MTBF): 1749682 h | Heat dissipation: 45.279 BTU/h | Switch type: Managed | Power over Ethernet (PoE): Yes | Power connector: DC-in jack | Copper ethernet cabling technology: 1000BASE-T | Weight: 337 g | Total Power over Ethernet (PoE) budget: 68 W | LED indicators: Yes | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | Basic switching RJ-45 Ethernet ports quantity: 8 | Product colour: Grey | AC input voltage: 100 - 240 V | Depth: 85 mm | Multicast support: Yes | Operating relative humidity (H-H): 10 - 95% | Power supply included: Yes | Storage relative humidity (H-H): 10 - 95% | Flow control support: Yes | Networking standards: IEEE 802.1Q | Networking standards: IEEE 802.3x | Networking standards: IEEE 802.3u | Networking standards: IEEE 802.3at | Networking standards: IEEE 802.3 | Networking standards: IEEE 802.3ab | Networking standards: IEEE 802.1p | Networking standards: IEEE 802.3az | Web-based management: Yes | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Width: 193 mm | 10G support: No | IGMP snooping: Yes | Switching capacity: 16 Gbit/s | Jumbo frames support: Yes | Networking standards: IEEE 802.3ad