



**TP-Link Outdoor
Pan/Tilt Security
Wi-Fi Camera
SPEC: 3K 5MP
(2880x1620),
2.4 GHz, 2
External
Antennas, 1
Ethernet Port,
Horizontal 360**

Modelis: Tapo C530WS

Gamintojas: TP-LINK

EAN: 8885020624984

Prekės kodas: 539876

73.99€

Reset button: Yes | Bluetooth: No | Antenna type: External | AC input voltage: 100 - 240 V | Tilt angle range: 60 - 130° | AC input frequency: 50/60 Hz | Product colour: White | Connectivity technology: Wired & Wireless | Audio output channels: 1.0 channels | Networking standards: IEEE 802.11g | Networking standards: IEEE 802.11n | Networking standards: IEEE 802.11ax | Networking standards: IEEE 802.11b | Sensor type (panoramic camera): CMOS | Manual: Yes | Operating relative humidity

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

(H-H): 10 - 90% | Depth: 90 mm | Antennas quantity: 2 | Package type: Box | Mounting kit: Yes | Protection features: Waterproof | Ethernet LAN: Yes | Wi-Fi standards: 802.11g | Wi-Fi standards: 802.11b | Siren noise level: 99 dB | Package height: 145 mm | Mirror: Yes | Wi-Fi standards: Wi-Fi 4 (802.11n) | Package width: 160 mm | Drilling template included: Yes | Video recording: Yes | Mounting type: Wall | Form factor: Turret | Maximum resolution: 2880 x 1620 pixels | Alert notification type: Push notification | Remotely operated: Yes | Type: IP security camera | Remote viewing: Yes | Storage temperature (T-T): -40 - 60 °C | International Protection (IP) code: IP66 | Compatible memory cards: MicroSD (TransFlash) | Built-in speaker(s): Yes | Operating temperature (T-T): -30 - 60 °C | Package depth: 210 mm | Camera tilt control: Yes | Width: 123.8 mm | Camera pan control: Yes | Lens viewing angle, horizontal: 95° | Audio detection: Yes | Motion sensor: Yes | Wi-Fi: Yes | Weatherproof: Yes | Mounting brackets included: Yes | Supported graphics resolutions: 2880 x 1620 | Built-in siren: Yes | Built-in microphone: Yes | Ethernet LAN (RJ-45) ports: 1 | Lens viewing angle, diagonal: 112° | Package weight: 710 g | Image quality adjustment: DNR | Audio system: 2-way | Power source type: AC, DC | Number of microphones: 1 | Live view: Yes | Auto pan mode: Yes | Storage relative humidity (H-H): 0 - 90% | Video motion detection: Yes | Lens viewing angle, vertical: 53° | Cloud-managed: Yes | Maximum operating distance: 29.9 m | Night vision: Yes | Placement supported: Outdoor | Number of cameras: 1 | Progressive scan: Yes | LED type: IR/White | Sensor type: CMOS | Frame rate: 30 fps | Video compression formats: H.264 | DC output voltage: 9 | Focal length range: 3.2 mm | Height: 123 mm | Maximum memory card size: 512 GB | Day/night mode: Yes | Audio formats supported: RTSP | Digital zoom: 12x | DC output current: 0.85 A | Total megapixels: 5 MP | Screws included: Yes | Audio input channels: 1.0 channels | HTTPS encryption: Yes | Optical sensor size: 25.4 / 3 mm (1 / 3") | Housing material: Metal