



**Optoma Photon
Life PK31
Standard throw
projector 900
ANSI lumens
DLP UHD 4K
(3840x2160) 3D
Black**

Modelis: E3PB011E111

Gamintojas: OPTOMA

EAN: 5055387668966

Prekės kodas: 539991

511.00€

Packaging content: Adaptor (150W) Remote control Basic user manual 2x AAA Battery HDMI Cable | Supported graphics resolutions: 1280 x 720 (HD 720) | Supported graphics resolutions: 1920 x 1080 (HD 1080) | Supported graphics resolutions: 3840 x 2160 | DC-in jack: Yes | Weight: 2.2 kg | AC input frequency: 50 - 60 Hz | AC input voltage: 100 - 240 V | Native aspect ratio: 16:9 | Cable lock slot: Yes | Product colour: Black | Commodity code: 8528620000 | Light source type: LED | On Screen Display (OSD) languages: Polish | On Screen Display (OSD) languages: Indonesian | High Dynamic Range (HDR) technology: Hybrid Log-Gamma (HLG) | On Screen Display (OSD) languages: Greek |

Uniformity: 90% | Projection distance: 1.99 - 5.47 m | On Screen Display (OSD) languages:

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

Vietnamese | On Screen Display (OSD) languages: Arabic | On Screen Display (OSD) languages: Portuguese | Service life of light source: 30000 h | On Screen Display (OSD) languages: Finnish | On Screen Display (OSD) languages: Simplified Chinese | On Screen Display (OSD) languages: Danish | On Screen Display (OSD) languages: Russian | On Screen Display (OSD) languages: Czech | High Dynamic Range (HDR) supported: Yes | On Screen Display (OSD) languages: Spanish | Throw ratio: 1.65:1 | Keystone correction, vertical: 40° | On Screen Display (OSD) languages: German | On Screen Display (OSD) languages: Italian | On Screen Display (OSD) languages: Dutch | Built-in speaker(s): Yes | USB 2.0 Type-A ports quantity: 1 | On Screen Display (OSD) languages: English | On Screen Display (OSD) languages: Norwegian | Projection technology: DLP | On Screen Display (OSD) languages: Swedish | Projector brightness: 900 ANSI lumens | On Screen Display (OSD) languages: Japanese | On Screen Display (OSD) languages: Hungarian | Supported aspect ratios: 4:3 | Supported aspect ratios: 16:9 | Offset: 105% | High Dynamic Range (HDR) technology: High Dynamic Range 10 (HDR10) | Number of OSD languages: 25 | Screen size compatibility: 1524 - 3810 mm (60 - 150") | On Screen Display (OSD) languages: Turkish | Remote control included: Yes | Keystone correction, horizontal: 40° | Projector native resolution: UHD 4K (3840x2160) | On Screen Display (OSD) languages: Traditional Chinese | On Screen Display (OSD) languages: French | RMS rated power: 5 W | On Screen Display (OSD) languages: Romanian | Zoom type: Manual | Interactive: No | Operating temperature (T-T): 0 - 35 °C | Smart projector: Yes | Package weight: 4.3 kg | Built-in display: No | Full HD: Yes | AC adapter included: Yes | Power consumption (max): 110 W | Card reader integrated: No | Power consumption (standby): 0.5 W | Product type: Standard throw projector | Cables included: USB | Vertical scan range: 15 - 255 Hz | Cable lock slot type: Kensington | Package width: 296 mm | Noise level: 32 dB | Zoom capability: Yes | Manual: Yes | On Screen Display (OSD): Yes | Power source: AC | Contrast ratio (typical): 200000:1 | Headphone outputs: 1 | HDMI ports quantity: 1 | Supported video modes: 480p | Supported video modes: 1080p | Horizontal scan range: 23 - 240 kHz | International Protection (IP) code: IP5X | Supported video modes: 2160p | Supported video modes: 480i | Supported video modes: 576i | Supported video modes: 720p | Placement: Desktop | 3D: Yes | Height: 130 mm | Focal length range: 15.8 - 17.4 mm | Width: 238 mm | Package depth: 396 mm | Quantity per pack: 1 pc(s) | HDMI version: 2.0 | Depth: 215 mm | Batteries included: Yes | Supported video modes: 1080i | Supported video modes: 576p | Package height: 198 mm