



ASUS TUF- GAMING-650B- EVO power supply unit 650 W 20+4 pin ATX ATX Black



Modelis: 90YE00D6-B0NA00

Gamintojas: ASUS

EAN: 4711636170550

Prekės kodas: 540059

62.99€

On/off switch: Yes | Combined power (+12V): 650 W | Package weight: 2.07 kg | Max output current (-12V): 0.3 A | Fan location: Top | Illumination: No | Bearing technology: DBB | Peripheral (Molex) power connectors (4-pin): 2 | PCI Express connector: Yes | Cables included: CPU, PCIe, Peripheral (Molex), SATA | Weight: 1.25 kg | Cabling type: Fully-Modular | Width: 140 mm | Max output current (+3.3V): 12 A | CPU power cable length: 65 cm | Number of fans: 1 fan(s) | Cooling type: Active | CPU power connector (4+4 pin): Yes | ATX version: 3.1 | Package width: 282 mm | Total power: 650 W | Motherboard power connector: 20+4 pin ATX | Package type: Box | Power protection features: Short circuit | Power protection features: Over voltage | Combined power (-12V): 3.6 W | Power protection features: Over power | Motherboard power cable length: 50 cm | Peripheral (Molex) power cable length: 400 | Package height: 127 mm | Package depth: 182 mm | Product colour: Black | Power supply unit (PSU) form factor: ATX | Power protection features: Overheating | Combined power

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

(+5V): 80 W | Power protection features: Under voltage | Peripheral (Molex) power cable length: 120 | Depth: 150 mm | Power protection features: Over current | Max output current (+5V): 12 A | 80 PLUS certification: 80 PLUS Bronze | Height: 86 mm | Combined power (+3.3V): 80 W | Max output current (+12V): 54.16 A | Combined power (+5Vsb): 15 W | Power Factor Correction (PFC) type: Active | Purpose: PC | SATA power cable length: 120 | Mean time between failures (MTBF): 120000 h | AC input voltage: 100 - 240 V | Max output current (+5Vsb): 3 A | Number of SATA power connectors: 4 | SATA power cable length: 400 | PCI Express power connectors (6+2 pin): 2