



# CyberPower PR750ELCD uninterruptible power supply (UPS) Line- Interactive 0.75 kVA 675 W 6 AC outlet(s)

Modelis: PR750ELCD

Gamintojas: CYBERPOWER

EAN: 4712364143397

Prekės kodas: 540130

## 348.00€

Certification: CE, EAC, RCM, RoHS | Battery recharge time: 8 h | Typical backup time at half load: 10.5 min | Output power capacity: 0.75 kVA | Input frequency: 50/60 Hz | Typical backup time at full load: 2.5 min | Harmonized System (HS) code: 8504408590 | AC outlet types: C13 coupler | EMI/RFI noise filtering: Yes | Maximum current: 10 A | Output operation voltage (min): 230 V | UPS topology: Line-Interactive | Surge energy rating: 405 J | Audible alarm modes: Alarm when on battery, Fault, Low battery alarm, Overload alarm | Surge protection: Yes | Output operation voltage (max): 230 V | Power factor: 0.9 | Hot-swap battery: Yes | Display type: LCD | Input operation voltage (min): 150 V | Input operation voltage (max): 301 V | Waveform: Pure sine | Operating temperature (T-T): 0 - 40 °C

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

| Form factor: Tower | USB port: Yes | Storage temperature (T-T): -15 - 45 °C | Depth: 138 mm | Response time: 4 ms | Weight: 12.3 kg | Package height: 283 mm | Audible alarm(s): Yes | Overload protection: Yes | Package width: 272 mm | AC outlets quantity: 6 AC outlet(s) | Battery technology: Sealed Lead Acid (VRLA) | Width: 349 mm | Power plug: C14 coupler | Storage relative humidity (H-H): 0 - 95% | Operating relative humidity (H-H): 0 - 95% | Product colour: Black | Number of batteries supported: 1 | Power protection features: Overload | Housing material: Metal | Output power: 675 W | LED indicators: Operation | LED indicators: Error | Height: 162 mm | Cables included: USB cable | Warnings: Keep away from sources of fire and water. | Warnings: Use the appliance in well-ventilated areas to avoid overheating. | Warnings: Do not disassemble the unit housing, there may be a risk of electric shock.