

CyberPower PR750ELCD uninterruptible power supply (UPS) Line-Interactive 0.75 kVA 675 W 6 AC outlet(s)

Gamintojas: **CYBERPOWER** · Modelis: **PR750ELCD** · EAN: **4712364143397** · Prekės kodas: **540130**



334,90 €

Kaina su PVM

Be PVM: 276,78 €

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Line-interactive UPS Topology
- ✓ Active PFC Compatible
- ✓ Automatic Voltage Regulation (AVR)
- ✓ Hot-swappable Batteries
- ✓ EMI and RFI Filtration
- ✓ USB Connectivity Port
- ✓ PowerPanel Management Software
- ✓ Tower Form Factor
- ✓ Energy Saving Technology
- ✓ Pure Sine Wave Output



Aprašymas

The Professional Tower Series UPS provides advanced level of power protection to servers, telecom equipments, VOIP, internet working hardware and other mission-critical applications. Featuring Pure Sine Wave output and Automatic Voltage Regulation (AVR) stabilizes the AC signal and maintains a safe voltage, it allows the UPS to maintain safe power levels for the connected equipment without resorting to battery power. The detachable, remote-controllable Multifunction LCD Readout can be mounted on the wall or in the control center nearby to provide highest convenience and flexibility under different management scenarios.

The optional SNMP/HTTP Remote Management Capability enables remote management and control of the system through standard web browser. Together with the included PowerPanel® Business Edition management software, it could provide corporate servers and critical workstations

comprehensive network power management including unattended-shutdown, event logging, reporting, and notifications.

Techninė specifikacija

Specifications	
Sandėlio grupė	UPS power supplies [+77][-127]
Features	
UPS topology	Line-Interactive
Output power capacity	0.75 kVA
Output power	675 W
Waveform	Pure sine
Input operation voltage (min)	150 V
Input operation voltage (max)	301 V
Input frequency	50/60 Hz
Output operation voltage (min)	230 V
Output operation voltage (max)	230 V
Maximum current	10 A
Surge energy rating	405 J
Response time	4 ms
Power factor	0.9
EMI/RFI noise filtering	Yes
Surge protection	Yes
Power protection features	Overload
Audible alarm(s)	Yes
Audible alarm modes	Alarm when on battery, Fault, Low battery alarm, Overload alarm
Ports & interfaces	
AC outlet types	C13 coupler
Power plug	C14 coupler
AC outlets quantity	6 AC outlet(s)
USB port	Yes
Battery	
Battery technology	Sealed Lead Acid (VRLA)
Number of batteries supported	1
Typical backup time at full load	2.5 min
Typical backup time at half load	10.5 min
Battery recharge time	8 h

Hot-swap battery	Yes
Design	
Form factor	Tower
Product colour	Black
Housing material	Metal
Display type	LCD
LED indicators	Error, Operation
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-15 - 45 °C
Operating relative humidity (H-H)	0 - 95%
Storage relative humidity (H-H)	0 - 95%
Certificates	
Certification	CE, EAC, RCM, RoHS
Packaging content	
Cables included	USB cable
Weight & dimensions	
Width	349 mm
Depth	138 mm
Height	162 mm
Weight	12.3 kg
Packaging data	
Package width	272 mm
Package depth	486 mm
Package height	283 mm
Package weight	13.3 kg
Logistics data	
Harmonized System (HS) code	8504408590
Country of origin	China
Other features	
Overload protection	Yes
Matmenys ir svoris	
Matmenys (I × P × A)	16,00cm × 14,00cm × 35,00cm
Svoris	12,30kg