

HP USB-C 100W G6 Dock

Gamintojas: **HEWLETT-PACKARD** · Modelis: **9X3V1UT** · EAN: **198415314048** · Prekės kodas: **540185**



127,90 €

Kaina su PVM

Be PVM: **105,70 €**

Sandėlyje



Prekė internetu

Nuskuokite kodą arba apsilankykite www.shopro.lt



Aprašymas

Compatibility: Tested and supported on select HP commercial PCs. For HP notebook compatibility please visit - <https://pcb.inc.hp.com/webapp/> !/us-en and search by notebook. Tested and supported on select 3rd party PCs. Contact your local sales representative to learn more. | Box contents: HP USB-C 100W G6 Dock 120 W power adapter Product notice Warranty card | Compatible operating systems: Windows 11 Windows 10 macOS Linux ThinPro ChromeOS | Bundled software: Poly Lens (Cloud, Desktop) | Cable lock slot type: Nano | Operating temperature (T-T): 0 - 35 °C | Product colour: Black | Ethernet LAN (RJ-45) ports: 1 | Package depth: 950 mm | HD type: 4K Ultra HD | Package weight: 1.09 kg | Pallet dimensions (W x D x H) (imperial): 1199.9 x 997.5 x 145 mm (47.2 x 39.3 x 5.71") | USB 3.2 Gen 2 (3.1 Gen 2) Type-A ports quantity: 1 | Windows operating systems supported: Windows 11 | Height: 51 mm | Microphone in: No | Operating relative humidity (H-H): 10 - 90% | HP segment: Business | Storage relative humidity (H-H): 5 - 95% | HDMI ports quantity: 1 | USB Power Delivery up to: 100 W | Package width: 396 mm | Colour name: Jet black | Width: 121 mm | Connectivity technology: Wired | DisplayPort version: 1.4 | Weight: 680 g | Other operating systems supported: ChromeOS | USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity: 2 | DisplayPorts quantity: 2 | Host interface: USB 3.2 Gen 2 (3.1 Gen 2) Type-C | Storage temperature (T-T): -20 - 60 °C | Maximum refresh rate: 120 Hz | Warranty card: Yes | Windows operating systems supported: Windows 10 | USB cable length: 1 m | Non-operating altitude: -15 - 12192 m | Linux operating systems supported: Yes | Cable lock slot: Yes | LED indicators: Power | Power supply: 120 W | Package height: 1710 mm | Mac operating systems supported: MacOS | Maximum digital resolution: 3840 x 2160 pixels | Ethernet LAN data rates: 25000 Mbit/s | Operating altitude: -15 - 3048 m | Card reader integrated: No | UNSPSC-code: 43211602 | HDMI version: 2.1 | Ethernet LAN: Yes | Pallet dimensions (W x D x H): 1200 x 1000 x 145 mm | Depth: 121 mm | Total carbon emissions, w/o use phase (kg of CO2e): 91 | Carbon emissions, end-of-life (kg of CO2e): 0.6 | Carbon emissions, manufacturing (kg of CO2e): 377 | General Product Safety Regulation (GPSR) URL: https://support.hp.com/us-en/document/ish_6126692-6126777-16?openCLC=true | Total carbon footprint (kg of CO2e): 522.6 | HP GTIN (EAN/UPC): 884962772355 | Carbon emissions, logistics (kg of CO2e): 50

Techninė specifikacija

Specifications	
Sandėlio grupė	Docking stations and port replicators [+12][[-9]
Matmenys ir svoris	
Matmenys (I × P × A)	10,00cm × 40,00cm × 17,00cm
Svoris	1,51kg