



ASUS Prime - 850G power supply unit 850 W 20+4 pin ATX ATX Black



Modelis: 90YE00U2-B0NA00

Gamintojas: ASUS

EAN: 4711636288194

Prekės kodas: 540254

160.99€

PCI Express power connectors (16-pin): 1 | Width: 150 mm | Purpose: PC | Peripheral (Molex) power connectors (4-pin): 4 | AC input voltage: 100 - 240 V | Cooling type: Active | Package weight: 2.88 kg | Height: 86 mm | Package width: 320 mm | On/off switch: Yes | Number of fans: 1 fan(s) | Package depth: 213 mm | Depth: 150 mm | Product colour: Black | 80 PLUS certification: 80 PLUS Gold | Power protection features: Under voltage | Power protection features: Over current | Power protection features: Short circuit | Power protection features: Over voltage | Cables included: CPU, PCIe, Peripheral (Molex), SATA | Package height: 113 mm | Power protection features: Over power | Power protection features: Overheating | Package type: Box | Weight: 1.48 kg | CPU power connector (4+4 pin): Yes | SATA power cable length: 400 | Illumination: No | Bearing technology: DBB | Combined power (+12V): 846 W | SATA power cable length: 120 | Total power: 850 W | Max output current (+5Vsb): 2.5 A | Max output current (+12V): 70.5 A | PCI Express power connectors (6+2 pin): 3 | ATX version: 3.1 | Combined power (+3.3V): 110 W | Number of SATA power connectors: 5 | Power

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

supply unit (PSU) form factor: ATX | Fan location: Top | PCI Express connector: Yes | Combined power (-12V): 3.6 W | Motherboard power connector: 20+4 pin ATX | Combined power (+5V): 110 W | Cabling type: Fully-Modular | Max output current (-12V): 0.3 A | Power Factor Correction (PFC) type: Active | PCI Express power cable length: 60 cm | Max output current (+5V): 20 A | Motherboard power cable length: 60 cm | Peripheral (Molex) power cable length: 150 mm | Peripheral (Molex) power cable length: 400 | Mean time between failures (MTBF): 120000 h | Combined power (+5Vsb): 12.5 W | Max output current (+3.3V): 20 A