



Keenetic Challenger SE (KN-3911) AX3000 Mesh Wi-Fi 6 Multi- Gigabit Router/Extender with Two 2.5 Gigabit Ethernet Ports

Modelis: KN-3911-01-EU

Gamintojas: KEENETIC

EAN: 4897082922254

Prekės kodas: 540297

103.00€

VPN support: PPTP (client/server), L2TP over IPSec client/server, OpenVPN client/server, SSTP client/server, IPsec VPN (client/server) | Supported WAN type: Multi-WAN | Supported protocols: EoIP, IP-IP, GRE | Quality of Service (QoS) support: Yes | Cables included: LAN (RJ-45) | Ethernet LAN: Yes | Command-line interface (CLI): Yes | Internal memory type: DDR4 | Operating relative humidity (H-H): 20 - 95% | Depth: 170 mm | Wi-Fi Multimedia (WMM)/(WME): Yes | Width: 170 mm | Internal memory:

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be

išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

512 MB | Processor cores: 2 | Processor model: MediaTek MT7981B | Top Wi-Fi standard: Wi-Fi 6 (802.11ax) | Backup function: Yes | IGMP snooping: Yes | Supported network protocols: IPoE, PPPoE, PPTP, L2TP, 802.1x | Traffic statistics: Yes | Ethernet WAN: Yes | Policy-based routing: Yes | Web-based setup wizard: Yes | Output current: 1.5 A | Schedule access: Yes | Antenna design: Internal | Height: 42 mm | Product type: Tabletop router | SSID-based VLAN assignment: Yes | Number of products included: 1 pc(s) | IPv4 & IPv6 features: IPv6 Telnet | SIM card slot: No | Wi-Fi band: Dual-band (2.4 GHz / 5 GHz) | USB port: No | Number of guest networks (2.4 GHz): 7 | Guest access: Yes | Bandwidth control: Yes | DSL WAN: No | IPv4 & IPv6 features: IPv6 SSH | IPv4 & IPv6 features: Dual stack IPv4/IPv6 | Captive portal: Yes | Cloud-managed: Yes | Housing material: Plastic | WLAN data transfer rate (first band): 300 Mbit/s | Processor manufacturer: MediaTek | Wall mountable: Yes | Output voltage: 12 V | WPS push button: Yes | Routing table: DHCP | Ping check: Yes | System event log: Yes | Firewall: Yes | MU-MIMO technology: Yes | DoS attack prevention: Yes | IntelliQoS: Yes | Universal Plug and Play (UPnP): Yes | Number of guest networks (5 GHz): 7 | Routing table: Manual | Direct or cloud access via KeenDNS: Yes | IPoE/PPPoE data rate: 4800 Mbit/s | WLAN data transfer rate (max): 3000 Mbit/s | HTTPS security for access via KeenDNS: Yes | Internet connection backup: Yes | WAN connection type: RJ-45, WISP | Cloudflare DNS: Yes | WireGuard throughput: 460 Mbit/s | AdGuard ad blocker: Yes | Intelligent Mesh technology: Yes | VPN server: OpenVPN | WLAN data transfer rate (second band): 2402 Mbit/s | Wi-Fi standards: Wi-Fi 6 (802.11ax) | Cabling technology: 10/100/1000/2500Base-T | Antennas quantity: 5 | Wi-Fi standards: Wi-Fi 5 (802.11ac) | Flash memory: 128 MB | Port forwarding: Yes | L2TP/PPTP data rate: 2400 Mbit/s | UDP-to-HTTP proxy: Yes | USSD request support: Yes | Built-in processor: Yes | 3G/4G USB modem compatibility: No | Mobile operating systems supported: Android | DHCP server: Yes | Ethernet LAN interface type: 2.5 Gigabit Ethernet | Firewall security: SPI | Dynamic DNS (DDNS): Yes | Mobile operating systems supported: iOS | WireGuard: Yes | PPPoE/PPTP/L2TP pass-through: Yes | Wi-Fi standards: Wi-Fi 4 (802.11n) | Number of users: 256 user(s) | Parental control: Yes | Number of data streams: 3x3 | Quick start guide: Yes | AC input frequency: 50/60 Hz | Firmware upgradeable: Yes | Ethernet LAN data rates: 10 | MIMO: Yes | Ethernet LAN data rates: 2500 Mbit/s | AC input voltage: 100 - 240 V | LED indicators: LAN, Power, WLAN | Operating temperature (T-T): 0 - 40 °C | Ethernet LAN (RJ-45) ports: 2 | Processor frequency: 1300 MHz | Weight: 385 g | DC-in jack: Yes | Ethernet LAN data rates: 100 Mbit/s | Product colour: White | AC adapter included: Yes | Ethernet LAN data rates: 1000 | Security algorithms: OWE | Security algorithms: WPA2-Enterprise | Networking standards: IEEE 802.11v | Security algorithms: WPA-PSK | Networking standards: IEEE 802.11k | Networking standards: IEEE 802.11g | Networking standards: IEEE 802.11n | DHCP client: Yes | Networking standards: IEEE 802.1Q | Networking standards: IEEE 802.11ax | Networking standards: IEEE 802.11a | Networking

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

standards: IEEE 802.11r | Security algorithms: WPA2-PSK | Web-based management: Yes | MAC address filtering: Yes | Security algorithms: WEP | Networking standards: IEEE 802.11b | Security algorithms: WPA3-PSK | Power source type: AC | Security algorithms: WPA3-Enterprise | Networking standards: IEEE 802.11ac | Network address translation (NAT): Yes