



GIGABYTE UD850GM PG5 V2 ICE Power Supply Unit- PCIe Gen 5.1, 80 PLUS Gold, Fully Modular Design, 120mm Fan, ATX 3.1 compatible, EU Plug

Modelis: GP-UD850GM PG5 ICE

Gamintojas: GIGABYTE

EAN: 4719331556457

Prekės kodas: 540311

107.99€

Number of EPS connectors: 2 | Peripheral (Molex) power cable length: 500 mm | PCI Express power connectors (12+4 pin) cable length: 700 mm | Floppy drive power connector: 1 | PCI Express connector: Yes | PCI Express power connectors (12+4 pin): 1 | Peripheral (Molex) power cable length:

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

150 mm | Warranty period: 10 year(s) | ATX version: 3.1 | Peripheral (Molex) power connectors (4-pin): 3 | AC input frequency: 50/60 Hz | Cooling type: Active | Fan diameter: 12 cm | PCI Express power connectors (6+2 pin): 4 | Bearing technology: HYB | Combined power (-12V): 3.6 W | Number of fans: 1 fan(s) | Package type: Box | AC input voltage: 100 - 240 V | Power factor: 0.9 | Input current: 12 - 6.5 A | Motherboard power cable length: 61 cm | Hold time: 16 ms | Power protection features: Under voltage | Power protection features: Over current | Power protection features: Overheating | Combined power (+3.3V): 105 W | Combined power (+5Vsb): 15 W | Power protection features: Short circuit | Power protection features: Over voltage | Max output current (+5Vsb): 3 A | Cabling type: Fully-Modular | Weight: 2.4 kg | Max output current (-12V): 0.3 A | Power protection features: Over power | Motherboard power connector: 20+4 pin ATX | Power Factor Correction (PFC) type: Active | 80 PLUS certification: 80 PLUS Gold | Product colour: White | SATA power cable length: 150 mm | SATA power cable length: 600 | Package weight: 2.56 kg | Max output current (+12V): 70.8 A | Number of SATA power connectors: 8 | Package width: 618 mm | Package depth: 269 mm | PCI Express power cable length: 60 cm | On/off switch: Yes | Power supply unit (PSU) form factor: ATX | Package height: 211 mm | Max output current (+5V): 20 A | Purpose: PC | CPU power connector (4+4 pin): Yes | Depth: 140 mm | Height: 86 mm | Efficiency: 90% | Mean time between failures (MTBF): 100000 h | Total power: 850 W | Max output current (+3.3V): 20 A | Combined power (+5V): 105 W | Width: 150 mm | CPU power cable length: 65 cm | Combined power (+12V): 850 W