



GIGABYTE P550SS ICE Power Supply - PCIe 5.0, 80 PLUS Silver, 120mm Fan, ATX 3.0 compatible, EU Plug

Modelis: GP-P550SS ICE

Gamintojas: GIGABYTE

EAN: 4719331554910

Prekės kodas: 540314

45.99€

Warranty period: 3 year(s) | Product colour: White | On/off switch: Yes | Package depth: 206 mm | Weight: 1.95 kg | Package height: 117 mm | Depth: 150 mm | Peripheral (Molex) power connectors (4-pin): 4 | AC input frequency: 50/60 Hz | Power protection features: Short circuit | Power protection features: Over voltage | Power protection features: Overheating | Power protection features: Over power | Power protection features: Under voltage | Power protection features: Over current | Total power: 550 W | Efficiency: 90% | Fan diameter: 12 cm | Package type: Box | Purpose: PC | Number of

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

fans: 1 fan(s) | Cooling type: Active | Package weight: 2.11 kg | 80 PLUS certification: 80 PLUS Silver | AC input voltage: 155-240 V | Input current: 6.3 A | Package width: 254 mm | Mean time between failures (MTBF): 100000 h | Width: 140 mm | Height: 86 mm | Floppy disk drive connector: Yes | Hold time: 16 ms | ATX version: 3.1 | Motherboard power cable length: 60 cm | PCI Express power connectors (6+2 pin): 2 | Combined power (+5Vsb): 15 W | Max output current (+3.3V): 20 A | Fan location: Top | Bearing technology: Ball bearing | Combined power (+3.3V): 100 W | Power Factor Correction (PFC) type: Active | Power supply unit (PSU) form factor: ATX | Max output current (+12V): 45.8 A | Combined power (-12V): 3.6 W | Cabling type: Non-Modular | Combined power (+5V): 100 W | Combined power (+12V): 549.6 W | ATX power connector (20+4 pin): Yes | Motherboard power connector: 20+4 pin ATX | Max output current (+5V): 20 A | Power Good signal delay range: 100 - 150 ms | CPU power connector (4+4 pin): Yes | Max output current (+5Vsb): 3 A | PCI Express connector: Yes | Max output current (-12V): 0.3 A | Floppy drive power connector: 2 | Number of SATA power connectors: 5