



TP-Link Omada 28-Port Gigabit L2+ Managed Switch with 24- Port PoE+



Modelis: TL-SG3428MP

Gamintojas: TP-LINK

EAN: 6935364010737

Prekės kodas: 540344

412.99€

Certification: CE, FCC, RoHS | User guide: Yes | Networking standards: IEEE 802.3z | Product colour: Black | Storage temperature (T-T): -40 - 70 °C | Width: 440 mm | Depth: 330 mm | Storage relative humidity (H-H): 5 - 90% | Quality of Service (QoS) support: Yes | Networking standards: IEEE 802.3i | Power over Ethernet (PoE): Yes | Operating relative humidity (H-H): 10 - 90% | AC input frequency: 50/60 Hz | Operating temperature (T-T): 0 - 45 °C | Security algorithms: SSL/TLS | Networking standards: IEEE 802.3af | Total Power over Ethernet (PoE) budget: 384 W | Networking standards: IEEE 802.3ab | Security algorithms: SSH | Networking standards: IEEE 802.3u | Web-based management: Yes | MAC address filtering: Yes | Number of fans: 2 fan(s) | AC input voltage: 100 - 240 V | Power source: AC | Networking standards: IEEE 802.3at | Form factor: 1U | Height: 44 mm | Power consumption (max): 480.1 W | LED indicators: Yes | Ethernet LAN data rates: 10,100,1000 Mbit/s | Quick start guide: Yes | Warnings: Ensure the unit is adequately ventilated during operation. | Warnings: Do not open the case or try to repair it yourself. | Warnings: The product is not suitable

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

for disposal in the regular waste bin. Take your used electronic equipment to a recycling centre in accordance with local regulations. | Rate limiting: Yes | IP-MAC-Port binding: Yes | Copper ethernet cabling technology: 10BASE-T | Basic switching RJ-45 Ethernet ports quantity: 24 | IGMP snooping: Yes | VLAN support: Yes | Management protocols: SNMPv1/v2c/v3, LLDP/LLDP-MED | Power over Ethernet (PoE) power per port: 30 W | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | SFP module slots quantity: 4 | Number of VLANs: 4000 | Authentication: MAC-based authentication, Port-based authentication | Configuring Location Settings (CLI): Yes | Link aggregation: Yes | Rack mounting: Yes | ARP inspection: Yes | Jumbo frames support: Yes | Gigabit Ethernet (copper) ports quantity: 24 | Copper ethernet cabling technology: 1000BASE-T | Head-of-line (HOL) blocking: Yes | Broadcast storm control: Yes | Static port security: Yes | 10G support: No | SSH/SSL support: Yes | Port mirroring: Yes | Power supply included: Yes | Loop protection: Yes | DHCP features: DHCPv6 snooping | System event log: Yes | IP routing: Yes | DHCP features: DHCP client | DHCP features: DHCP relay | Flow control support: Yes | Virtual LAN features: MAC address-based VLAN | Virtual LAN features: Voice VLAN | Switching capacity: 56 Gbit/s | Virtual LAN features: Tagged VLAN | Power connector: AC-in jack | Power over Ethernet plus (PoE+) ports quantity: 24 | Forwarding rate: 41.66 Mpps | BPDU filtering/protection: Yes | DHCP features: DHCP server | DHCP features: DHCP snooping | Switch type: Managed | Active link detection: Yes | Heat dissipation: 1637.14 BTU/h | Virtual LAN features: Private VLAN | Multicast support: Yes | Virtual LAN features: Port-based VLAN | Access Control List (ACL): Yes | DHCP features: DHCPv6 client | Switch layer: L2+ | Console port: RJ-45/micro-USB | Cloud-managed: Yes | GARP VLAN Registration Protocol (GVRP): Yes | MAC address table: 16000 entries | Packet buffer memory: 12 MB | Spanning tree protocol: Yes | Jumbo frames: 9000 | Store-and-forward: Yes | Export Control Classification Number (ECCN): EAR99