



TP-Link Tapo Pan/Tilt AI Home Security Wi-Fi Camera



Modelis: C260

Gamintojas: TP-LINK

EAN: 8885021370088

Prekės kodas: 540444

67.99€

Sensor type: CMOS | DC output current: 2 A | Camera tilt control: Yes | Camera pan control: Yes | Progressive scan: Yes | Intelligent Video Surveillance (IVS) system features: Line crossing detection | Intelligent Video Surveillance (IVS) system features: Vehicle detection | Number of sensors: 1 | Intelligent Video Surveillance (IVS) system features: Face detection | Intelligent Video Surveillance (IVS) system features: Human detection | Intelligent Video Surveillance (IVS) system features: Pet detection | Alert notification type: Push notification, Snapshot alert message | Minimum aperture number: 1.6 | Focal length range: 4.3 mm | Remote viewing: Yes | Day/night mode: Yes | Built-in speaker(s): Yes | Maximum aperture number: 1.6 | Privacy protection: Yes | Cloud-managed: Yes | Video recording: Yes | Video compression formats: H.264 | Image quality adjustment: DNR | Mounting type: Ceiling/Wall/Desk | Video motion detection: Yes | Infrared (IR) cut-off filter: Yes | Virtual assistant: Amazon Alexa & Google Assistant | Management software: Tapo App | Placement supported: Indoor | Optical sensor size: 25.4 / 2.7 mm (1 / 2.7") | Infra-red wavelength: 850 nm | Live view: Yes | Noise reduction: Yes | DC output voltage: 5 | Night vision: Yes | Frame rate: 25 fps |

Maximum memory card size: 512 GB | Number of lenses: 1 | Mobile operating systems supported:

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

iOS 11.0 | Mobile operating systems supported: Android 5.0 | Built-in siren: Yes | Lens viewing angle, diagonal: 109.6° | Customs product code (TARIC): 8525890000 | Lens viewing angle, horizontal: 91.5° | Siren noise level: 90 dB | Lens viewing angle, vertical: 46.1° | Height: 74.6 mm | Reset button: Yes | Package height: 121.5 mm | Card reader integrated: Yes | Operating temperature (T-T): 0 - 40 °C | Audio system: 2-way | Wi-Fi standards: 802.11g | Package type: Box | Product colour: White | Number of illumination LEDs: 2 | Operating relative humidity (H-H): 10 - 90% | Ethernet LAN: No | AC input voltage: 100-240 V | Wide Dynamic Range (WDR): Yes | Compliance certificates: CE | Supported graphics resolutions: 3840 x 2160 | Width: 88.7 mm | Night vision distance: 12 m | Depth: 118.9 mm | Supported network protocols: TCP/IP, DHCP, ICMP, DNS, NTP, HTTPS, TCP, UDP | Audio formats supported: RTSP | Storage temperature (T-T): -20 - 60 °C | AC input frequency: 50/60 Hz | Cable length: 3 m | Wi-Fi standards: Wi-Fi 4 (802.11n) | Zoom capability: Yes | Maximum resolution: 3840 x 2160 pixels | Package width: 105.5 mm | Wi-Fi: Yes | Connectivity technology: Wireless | Package depth: 181.5 mm | Total megapixels: 8 MP | Supported video modes: 2160p | Bluetooth: Yes | Power consumption (typical): 2.5 W | Number of cameras: 1 | Weight: 220 g | Power consumption (max): 8.65 W | Wi-Fi standards: 802.11b | Security algorithms: WPA3 | Storage relative humidity (H-H): 5 - 90% | Package weight: 580 g | LED type: IR | Security algorithms: SSL/TLS | Security algorithms: WPA | Networking standards: IEEE 802.11g | Networking standards: IEEE 802.11n | Type: IP security camera | Security algorithms: WPA2-PSK | Compatible memory cards: MicroSD (TransFlash) | Video formats supported: H.264 | Networking standards: IEEE 802.11b | Security algorithms: 128-bit AES | Compliance certificates: Federal Communications Commission (FCC) | Power source type: AC, DC | Built-in microphone: Yes