



Ubiquiti UniFi Pro XG 10 PoE Managed L2/L3 10G Ethernet (100/1000/10000) Power over Ethernet (PoE) 1U Grey

Modelis: USW-Pro-XG-10-PoE

Gamintojas: UBIQUITI

EAN: 810177160137

Prekės kodas: 540467

754.99€

10G Ethernet (copper) ports quantity: 10 | Compliance certificates: Federal Communications Commission (FCC) | Power supply included: Yes | IPv4 routes: 12000 | Compliance certificates: Industry Canada (IC) | Compliance certificates: National Defense Authorization Act (NDAA) | 10G support: Yes | Number of VLANs: 1000 | Basic switching RJ-45 Ethernet ports type: 10G Ethernet (100/1000/10000) | Compliance certificates: CE | Basic switching RJ-45 Ethernet ports quantity: 10 | Jumbo frames support: Yes | Switching capacity: 240 Gbit/s | Power over Ethernet 4PPoE (PoE++) ports quantity: 10 | Power connector: AC/DC | MAC address table: 32000 entries | Rate limiting: Yes | Switch layer: L2/L3 | DHCP features: DHCP server | SFP+ module slots quantity: 2 | Stackable: Yes |

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

Packet buffer memory: 2 MB | Loop protection: Yes | DHCP features: DHCP relay | IGMP snooping: Yes | Static route: Yes | Switch type: Managed | DHCP features: DHCP guarding | Power over Ethernet (PoE) type supported: PoE++ (4PPoE) | Virtual LAN features: Interface-based VLAN | Multicast support: Yes | Virtual LAN features: Voice VLAN | DHCP features: DHCPv6 snooping | Port mirroring: Yes | Broadcast storm control: Yes | Backlight display: Yes | Throughput: 120 Gbit/s | Forwarding rate: 179 Mpps | Rack mount kit: Yes | Flow control support: Yes | Operating temperature (T-T): -5 - 40 °C | VLAN support: Yes | Form factor: 1U | Total Power over Ethernet (PoE) budget: 400 W | Rack mounting: Yes | Power over Ethernet (PoE): Yes | Redundant power supply (RPS) support: Yes | Housing material: SGCC | Cables included: Power | AC input frequency: 50/60 Hz | Width: 442.4 mm | Manual: Yes | Operating relative humidity (H-H): 10 - 90% | Power consumption (max): 520 W | Reset button: Yes | Weight: 4.6 kg | Height: 44 mm | Display type: LCM | Quality of Service (QoS) support: Yes | Depth: 285 mm | Power over Ethernet (PoE) power per port: 15.4 W | Product colour: Grey | AC input voltage: 100 - 240 V | LED indicators: System | Power source: AC/DC