

Ubiquiti UniFi Pro XG 10 PoE Managed L2/L3 10G Ethernet (100/1000/10000) Power over Ethernet (PoE) 1U Grey

Gamintojas: **UBIQUITI** · Modelis: **USW-Pro-XG-10-PoE** · EAN: **810177160137** · Prekės kodas: **540467**



809,90 €

Kaina su PVM


Be PVM: **669,34 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt



Aprašymas

SFP+ module slots quantity: 2 | Static route: Yes | Switch type: Managed | Loop protection: Yes | Flow control support: Yes | Power over Ethernet 4PPoE (PoE++) ports quantity: 10 | Forwarding rate: 179 Mpps | Throughput: 120 Gbit/s | Switch layer: L2/L3 | 10G Ethernet (copper) ports quantity: 10 | Rate limiting: Yes | Broadcast storm control: Yes | Backlight display: Yes | Rack mount kit: Yes | Compliance certificates: National Defense Authorization Act (NDAA) | IPv4 routes: 12000 | Compliance certificates: CE | Port mirroring: Yes | Multicast support: Yes | Compliance certificates: Federal Communications Commission (FCC) | Stackable: Yes | Compliance certificates: Industry Canada (IC) | Power over Ethernet (PoE) type supported: PoE++ (4PPoE) | Virtual LAN features: Interface-based VLAN | Virtual LAN features: Voice VLAN | Operating temperature (T-T): -5 - 40 °C | Jumbo frames support: Yes | Power supply included: Yes | Manual: Yes | Weight: 4.6 kg | AC input frequency: 50/60 Hz | Reset button: Yes | Power connector: AC/DC | DHCP features: DHCPv6 snooping | DHCP features: DHCP server | DHCP features: DHCP guarding | Power consumption (max): 520 W | Depth: 285 mm | MAC address table: 32000 entries | Rack mounting: Yes | Power over Ethernet (PoE): Yes | Form factor: 1U | DHCP features: DHCP relay | Packet buffer memory: 2 MB | 10G support: Yes | Number of VLANs: 1000 | Quality of Service (QoS) support: Yes | Total Power over Ethernet (PoE) budget: 400 W | Switching capacity: 240 Gbit/s | Height: 44 mm | LED indicators: System | Product colour: Grey | AC input voltage: 100 - 240 V | Cables included: Power | Power over Ethernet (PoE) power per port: 15.4 W | Redundant power supply (RPS) support: Yes | Housing material: SGCC | Basic switching RJ-45 Ethernet ports type: 10G Ethernet (100/1000/10000) | Display type: LCM | Operating relative humidity (H-H): 10 - 90% | VLAN support: Yes | IGMP snooping: Yes | Basic switching RJ-45 Ethernet ports quantity: 10 | Power source: AC/DC | Width: 442.4 mm

Techninė specifikacija

Specifications

Sandėlio grupė	Managed [+67][−103]
----------------	---------------------

Matmenys ir svoris

Matmenys (I × P × A)	12,00cm × 40,00cm × 52,00cm
----------------------	-----------------------------

Svoris	5,80kg
--------	--------