



GIGABYTE B550M DS3H AC R2 Motherboard - AMD Ryzen 5000 CPUs, 5+3 Phases VRM, up to 4733MHz DDR4 (O.C.), 1xPCIe 4.0 + 1xPCIe 3.0 M.2, Wi-Fi 5, 1GbE LAN, USB 3.2 Gen 1

Modelis: B550M DS3H AC R2

Gamintojas: GIGABYTE

EAN: 4719331869908

Prekės kodas: 540579

116.99€

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš išsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

Bundled software: Norton® Internet Security (OEM version) LAN bandwidth management software | Compatible processor series: AMD Ryzen 5000 Series | Supported memory clock speed (max): 4733 MHz | Compatible processor series: AMD Ryzen 3000 Series | Products per shipping (inner) case: 1 pc(s) | Processor manufacturer: AMD | Compatible processor series: AMD Ryzen 4000 Series | Wi-Fi standards: 802.11a | Wi-Fi standards: 802.11g | Wi-Fi standards: 802.11b | Headphone outputs: 1 | Battery type: CR2032 | Wi-Fi standards: Wi-Fi 5 (802.11ac) | Wi-Fi: Yes | Bluetooth version: 5.0 | Warranty period: 3 year(s) | Number of storage drives supported: 6 | Number of battery cells: 1 | Battery weight: 3 g | Supported memory types: DDR4-SDRAM | Antenna included: Yes | Wi-Fi standards: Wi-Fi 4 (802.11n) | Height: 35 mm | Number of memory slots: 4 | Batteries included: Yes | Memory channels: Dual-channel | HDMI version: 2.1 | Depth: 244 mm | WiFi-AP antenna jack: 2 | Ethernet LAN: Yes | Ethernet interface type: Gigabit Ethernet | Desktop Management Interface (DMI) version: 2.7 | Memory slots type: DIMM | Top Wi-Fi standard: Wi-Fi 5 (802.11ac) | PCI Express x16 (Gen 4.x) slots: 1 | Screws included: Yes | Processor socket: Socket AM4 | HDMI ports quantity: 1 | Battery technology: Lithium-Manganese Dioxide (LiMnO2) | RGB LED pin header: Yes | Microphone in: Yes | On-board graphics card: No | Line-in: Yes | PS/2 ports quantity: 1 | Width: 244 mm | Number of HDDs supported: 4 | WLAN controller model: Realtek RTL8821CE | Audio output channels: 7.1 channels | Supported memory clock speeds: 3200 MHz | Supported memory clock speeds: 4266 | Audio chip: Realtek ALC1220-VB | Supported memory clock speeds: 2667 | Supported memory clock speeds: 3733 | Supported memory clock speeds: 4400 | Supported memory clock speeds: 3466 | Supported memory clock speeds: 4133 | Supported memory clock speeds: 4000 | Supported memory clock speeds: 3400 | Supported memory clock speeds: 3866 | Maximum internal memory: 128 GB | PC health monitoring: Voltage | Supported memory clock speeds: 2933 | Supported memory clock speeds: 3600 | Supported memory clock speeds: 4733 | Product colour: Dark brown | Supported memory clock speeds: 2400 | PC health monitoring: Fan | Supported memory clock speeds: 4600 | Supported memory clock speeds: 2133 | PC health monitoring: Temperature | Unbuffered memory: Yes | Supported storage drive interfaces: M.2, PCI Express 3.0, PCI Express 4.0, SATA III | Motherboard chipset: AMD B550 | Bluetooth: Yes | LAN controller: Realtek RTL8111H | HDCP: Yes | Lithium weight per battery: 0.07 g | Supported storage drive types: HDD & SSD | DirectX version: 12.0 | Number of SATA III connectors: 4 | Ethernet LAN (RJ-45) ports: 1 | RAID levels: 10 | ECC compatibility: ECC & Non-ECC | RAID levels: 0 | RAID levels: 1 | 1st M.2 highest PCI Express generation: 4.0 | Package width: 270 mm | Maximum resolution: 5120 x 2880 pixels | Package depth: 268 mm | TPM connector: Yes | PCI Express x1 (Gen 3.x) slots: 1 | Cooling type: Passive | ATX Power connector (24-pin): Yes | Windows operating systems supported: Windows 10 x64 | Clear CMOS

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

jumper: Yes | Supported processor sockets: Socket AM4 | 1st M.2 largest key size: 2280 | Serial port headers: 1 | EPS power connector (8-pin): Yes | Package weight: 1.07 kg | Windows operating systems supported: Windows 11 x64 | 2nd M.2 largest key size: 2280 | 2nd M.2 highest PCI Express generation: 3.0 | PCI Express x16 (Gen 3.x) slots: 1 | Package height: 68 mm | Maximum internal memory per slot: 32 GB | Front panel connector: Yes | DisplayPort version: 1.4 | Number of chassis fan connectors: 2 | Number of CPU fan connectors: 1 | USB 3.2 Gen 1 (3.1 Gen 1) connectors: 2 | USB 2.0 ports quantity: 2 | Front panel audio connector: Yes | Number of M.2 (M) slots: 2 | BIOS type: UEFI AMI | Number of EPS power connectors (8-pin): 1 | Weight: 980 g | USB 2.0 connectors: 1 | CPU fan connector: Yes | Power source type: ATX | Parallel processing technology support: Not supported | Motherboard chipset family: AMD | RAID support: Yes | DisplayPorts quantity: 1 | USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity: 4 | Motherboard form factor: micro ATX | Number of RGB LED pin headers: 5