



TP-Link 28-Port Gigabit Easy Smart Switch with 24-Port PoE+



Modelis: TL-SG1428PE

Gamintojas: TP-LINK

EAN: 1210002617123

Prekės kodas: 540617

247.99€

Certification: CE, FCC, RoHS | Cable types supported: Cat5 | Cable types supported: Cat5e | Cable types supported: Cat3 | Cable types supported: Cat4 | Cable types supported: Cat6 | Forwarding rate: 41.7 Mpps | Rack mount kit: Yes | Number of queues: 4 | Virtual LAN features: Port-based VLAN | Fiber ethernet cabling technology: 1000BASE-X | Virtual LAN features: Tagged VLAN | Gigabit Ethernet (copper) ports quantity: 26 | Jumbo frames: 10000 | Link aggregation: Yes | Multicast support: Yes | Power over Ethernet (PoE) power per port: 30 W | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Copper ethernet cabling technology: 1000BASE-T | Power supply included: Yes | Copper ethernet cabling technology: 10BASE-T | VLAN support: Yes | Rate limiting: Yes | Basic switching RJ-45 Ethernet ports quantity: 26 | Switch layer: L2 | SFP module slots quantity: 2 | Copper ethernet cabling technology: 100BASE-TX | MAC address table: 8000 entries | Auto-negotiation: Yes | Packet buffer memory: 4.1 MB | Port mirroring: Yes | 10G support: No | Number of VLANs: 32 | Power over Ethernet plus (PoE+) ports quantity: 24 | Harmonized System

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

(HS) code: 85176990 | Flow control support: Yes | IGMP snooping: Yes | Switch type: Managed | Store-and-forward: Yes | Jumbo frames support: Yes | Broadcast storm control: Yes | Switching capacity: 56 Gbit/s | Rack mounting: Yes | Package depth: 528 mm | Package height: 100 mm | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | Product colour: Black | Width: 440 mm | User guide: Yes | Total Power over Ethernet (PoE) budget: 250 W | Power consumption (max): 1039.03 W | Power over Ethernet (PoE): Yes | Operating temperature (T-T): 0 - 50 °C | Operating relative humidity (H-H): 10 - 90% | Number of fans: 2 fan(s) | AC input frequency: 50 - 60 Hz | Networking standards: IEEE 802.3at | Security algorithms: SNMPv2 | Storage relative humidity (H-H): 5 - 90% | Networking standards: IEEE 802.3af | Networking standards: IEEE 802.3 | Networking standards: IEEE 802.3ab | Networking standards: IEEE 802.1p | Networking standards: IEEE 802.1Q | Networking standards: IEEE 802.3x | Web-based management: Yes | Networking standards: IEEE 802.3u | Security algorithms: SNMPv3 | Security algorithms: SNMP | Power source: AC | AC input voltage: 100 - 240 V | Form factor: 1U | Package width: 336 mm | Depth: 220 mm | Package weight: 2.29 kg | Height: 44 mm | Cables included: AC | Auto MDI/MDI-X: Yes