

TP-Link 28-Port Gigabit Easy Smart Switch with 24-Port PoE+

Gamintojas: **TP-LINK** · Modelis: **TL-SG1428PE** · EAN: **1210002617123** · Prekės kodas: **540617**



285,90 €

Kaina su PVM

Be PVM: **236,28 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt



Aprašymas

Certification: CE, FCC, RoHS | Virtual LAN features: Tagged VLAN | Virtual LAN features: Port-based VLAN | Number of queues: 4 | Gigabit Ethernet (copper) ports quantity: 26 | Jumbo frames: 10000 | Fiber ethernet cabling technology: 1000BASE-X | Link aggregation: Yes | Cable types supported: Cat5 | Cable types supported: Cat5e | Cable types supported: Cat4 | Forwarding rate: 41.7 Mpps | Rack mount kit: Yes | Cable types supported: Cat3 | Cable types supported: Cat6 | Power over Ethernet plus (PoE+) ports quantity: 24 | Switch layer: L2 | Power supply included: Yes | Multicast support: Yes | IGMP snooping: Yes | Number of VLANs: 32 | Jumbo frames support: Yes | Rate limiting: Yes | Switch type: Managed | MAC address table: 8000 entries | Auto-negotiation: Yes | Flow control support: Yes | Packet buffer memory: 4.1 MB | Port mirroring: Yes | Harmonized System (HS) code: 85176990 | Broadcast storm control: Yes | Store-and-forward: Yes | SFP module slots quantity: 2 | Switching capacity: 56 Gbit/s | Copper ethernet cabling technology: 100BASE-TX | 10G support: No | Copper ethernet cabling technology: 10BASE-T | Copper ethernet cabling technology: 1000BASE-T | VLAN support: Yes | Basic switching RJ-45 Ethernet ports quantity: 26 | Power over Ethernet (PoE) power per port: 30 W | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Package weight: 2.29 kg | Height: 44 mm | Networking standards: IEEE 802.3 | Cables included: AC | Networking standards: IEEE 802.3af | Networking standards: IEEE 802.3u | AC input frequency: 50 - 60 Hz | Form factor: 1U | Package height: 100 mm | Web-based management: Yes | Depth: 220 mm | Operating relative humidity (H-H): 10 - 90% | Package width: 336 mm | AC input voltage: 100 - 240 V | Operating temperature (T-T): 0 - 50 °C | Total Power over Ethernet (PoE) budget: 250 W | Power source: AC | Number of fans: 2 fan(s) | Auto MDI/MDI-X: Yes | Networking standards: IEEE 802.1Q | Networking standards: IEEE 802.3x | Storage relative humidity (H-H): 5 - 90% | Power over Ethernet (PoE): Yes | Security algorithms: SNMP | Width: 440 mm | Rack mounting: Yes | User guide: Yes | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | Security algorithms: SNMPv3 | Package depth: 528 mm | Networking standards: IEEE 802.3ab | Networking standards: IEEE 802.1p | Power consumption (max): 1039.03 W | Product colour: Black | Networking standards: IEEE 802.3at | Security algorithms: SNMPv2

Techninė specifikacija

Specifications	
Sandėlio grupė	Switches [+83][-71]
Matmenys ir svoris	
Matmenys (I × P × A)	34,00cm × 11,00cm × 54,00cm
Svoris	4,40kg