



Dahua Technology IPC- HFW2849TL-S- LED-0280B-PRO - fixed-focus bullet network camera with WizSense technology

Modelis: IPC-HFW2849TL-S-LED-0280B-PRO

Gamintojas: DAHUA

EAN: 6939554956478

Prekės kodas: 540677

148.00€

Certification: CE-LVD: EN62368-1 CE-EMC: Electromagnetic Compatibility Directive 2014/30/EU | Mobile operating systems supported: iOS | Mounting type: Ceiling/Wall/Pole | Mirror: Yes | Power consumption (Power over Ethernet (PoE)): 3.2 W | Noise reduction technology: 3D noise reduction | Sensor type: CMOS | Management software: Smart PSS Lite DSS DMSS | Night vision: Yes | Mobile operating systems supported: Android | Video compression formats: H.264H | Video compression formats: H.264 | ROM capacity: 128 MB | Number of lenses: 3 | Frame rate: 30 fps | Pan range: 0 -

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

360° | Voice codecs: G.711Mu | Video compression formats: H.264B | Day/night mode: Yes | Video compression formats: MJPEG | RAM capacity: 256 MB | Camera shutter type: Electronic | Video compression formats: H.265 | Bit rate control: Constant Bit Rate (CBR)/Variable Bit Rate (VBR) | Camera shutter speed: 1/3 - 1/100000 s | Region of Interest (ROI) encoding: Yes | Total megapixels: 8 MP | Progressive scan: Yes | Voice codecs: PCM | Video motion detection: Yes | Built-in HDD: No | Placement supported: Indoor & outdoor | Number of users: 20 user(s) | Voice codecs: G.711a | Voice codecs: G.726 | Operating relative humidity (H-H): 0 - 95% | International Protection (IP) code: IP67 | Networking standards: IEEE 802.3af | White balance: Auto | Power consumption (max): 6.1 W | Number of illumination LEDs: 4 | White balance: Outdoor | White balance: Street lamp | Number of cameras: 1 | Built-in light: Yes | Type: IP security camera | White balance: Natural | Form factor: Bullet | Bit rate: H.264: 32 kbps-8192 kbps H.265: 12 kbps-8192 kbps | Angle of rotation: 360° | Night vision distance: 50 m | Ethernet LAN (RJ-45) ports: 1 | Operating temperature (T-T): -40 - 60 °C | Supported network protocols: IPv4 IPv6 HTTP TCP UDP ARP RTP RTSP RTCP RTMP SMTP FTP SFTP DHCP DNS DDNS QoS UPnP NTP Multicast ICMP IGMP NFS PPPoE P2P Bonjour Auto Registration | Weight: 570 g | Maximum resolution: 3840 x 2160 pixels | Wide Dynamic Range (WDR): Yes | Housing material: Metal | Product colour: White | Storage temperature (T-T): -40 - 60 °C | Power consumption (typical): 2.3 W | Depth: 197.9 mm | Highlight Compensation (HLC): Yes | Height: 76.2 mm | White balance: Manual | White balance: Custom modes | Supported graphics resolutions: 352 x 240 | Supported graphics resolutions: 2304 x 1296 | Supported graphics resolutions: 704 x 576 | Supported graphics resolutions: 3072 x 2048 | Supported graphics resolutions: 352 x 288 | Supported graphics resolutions: 2048 x 1536 | Supported graphics resolutions: 3072 x 1728 | Power source type: DC, PoE | Tilt angle range: 0 - 90° | Width: 80.2 mm | Supported graphics resolutions: 1280 x 720 | Supported graphics resolutions: 2880 x 1620 | Supported graphics resolutions: 704 x 480 | Supported graphics resolutions: 2688 x 1520 | Supported graphics resolutions: 1920 x 1080 | Supported graphics resolutions: 640 x 480 | Supported graphics resolutions: 1280 x 960 | Connectivity technology: Wired | Supported graphics resolutions: 3840 x 2160 | Number of Privacy masking areas: 4 | Max power consumption (Power over Ethernet (PoE)) : 7,4 W