

Dahua Technology IPC-HFW2849TL-S-LED-0280B-PRO - fixed-focus bullet network camera with WizSense technology

Gamintojas: **DAHUA** · Modelis: **IPC-HFW2849TL-S-LED-0280B-PRO** · EAN: **6939554956478** · Prekės kodas: **540677**



145,90 €

Kaina su PVM

Be PVM: **120,58 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt



Aprašymas

Certification: CE-LVD: EN62368-1 CE-EMC: Electromagnetic Compatibility Directive 2014/30/EU | Progressive scan: Yes | Power consumption (Power over Ethernet (PoE)): 3.2 W | Voice codecs: G.711a | Voice codecs: G.726 | Mounting type: Ceiling/Wall/Pole | Voice codecs: PCM | Pan range: 0 - 360° | Voice codecs: G.711Mu | Noise reduction technology: 3D noise reduction | Night vision: Yes | Management software: Smart PSS Lite DSS DMSS | Placement supported: Indoor & outdoor | Mobile operating systems supported: iOS | Number of lenses: 3 | Sensor type: CMOS | ROM capacity: 128 MB | Mobile operating systems supported: Android | Video compression formats: MJPEG | Video motion detection: Yes | Day/night mode: Yes | Number of users: 20 user(s) | Video compression formats: H.265 | Camera shutter speed: 1/3 - 1/100000 s | Video compression formats: H.264 | Video compression formats: H.264H | Total megapixels: 8 MP | Frame rate: 30 fps | Mirror: Yes | Bit rate control: Constant Bit Rate (CBR)/Variable Bit Rate (VBR) | Region of Interest (ROI) encoding: Yes | Camera shutter type: Electronic | RAM capacity: 256 MB | Video compression formats: H.264B | Built-in HDD: No | Operating temperature (T-T): -40 - 60 °C | Bit rate: H.264: 32 kbps-8192 kbps H.265: 12 kbps-8192 kbps | Maximum resolution: 3840 x 2160 pixels | Form factor: Bullet | Night vision distance: 50 m | Built-in light: Yes | Ethernet LAN (RJ-45) ports: 1 | Supported graphics resolutions: 3072 x 1728 | Supported graphics resolutions: 352 x 240 | Supported graphics resolutions: 2304 x 1296 | Number of illumination LEDs: 4 | Supported graphics resolutions: 1280 x 720 | Supported graphics resolutions: 2880 x 1620 | Product colour: White | Storage temperature (T-T): -40 - 60 °C | Supported graphics resolutions: 640 x 480 | Supported graphics resolutions: 704 x 576 | Supported graphics resolutions: 1280 x 960 | Supported graphics resolutions: 3840 x 2160 | Supported graphics resolutions: 352 x 288 | Supported graphics resolutions: 704 x 480 | Supported graphics resolutions: 2688 x 1520 | Supported graphics resolutions: 1920 x 1080 | Width: 80.2 mm | Power consumption (typical): 2.3 W | Highlight Compensation (HLC): Yes | Supported graphics resolutions: 2048 x 1536 | Power consumption (max): 6.1 W | Weight: 570 g | Networking standards: IEEE 802.3af | White balance: Auto | Type: IP security camera | White balance: Natural | International Protection (IP) code: IP67 | Number of cameras: 1 | Operating relative humidity (H-H): 0 - 95% | Power source type: DC, PoE | Connectivity technology: Wired | Housing material: Metal | Wide

Dynamic Range (WDR): Yes | Supported graphics resolutions: 3072 x 2048 | White balance: Street lamp | Supported network protocols: IPv4 IPv6 HTTP TCP UDP ARP RTP RTSP RTCP RTMP SMTP FTP SFTP DHCP DNS DDNS QoS UPnP NTP Multicast ICMP IGMP NFS PPPoE P2P Bonjour Auto Registration | White balance: Custom modes | Angle of rotation: 360° | Tilt angle range: 0 - 90° | White balance: Manual | Height: 76.2 mm | Depth: 197.9 mm | White balance: Outdoor | Max power consumption (Power over Ethernet (PoE)) : 7,4 W | Number of Privacy masking areas: 4

Techninė specifikacija

Matmenys ir svoris	
Matmenys (l × p × a)	12,00cm × 24,00cm × 11,00cm
Svoris	0,70kg