



# Dahua Technology IPC- HDW2849T-S- LED-0280B-PRO



Modelis: HDW2849T-S-LED-0280B-PRO

Gamintojas: DAHUA

EAN: 6939554956430

Prekės kodas: 540678

## 149.99€

Certification: ONVIF (Profile S/G/T) | Maximum resolution: 3840 x 2160 pixels | Connectivity technology: Wired | Supported graphics resolutions: 352 x 288 | Supported graphics resolutions: 640 x 480 (VGA) | Supported graphics resolutions: 2688 x 1520 | Supported graphics resolutions: 352 x 240 | Supported graphics resolutions: 2304 x 1296 | Supported graphics resolutions: 704 x 576 | Power source type: DC, PoE | Built-in light: Yes | Weight: 420 g | Product colour: White | Networking standards: IEEE 802.3af | Bit rate: H.264: 32 kbps-8192 kbps H.265: 12 kbps-8192 kbps | Supported graphics resolutions: 3840 x 2160 | Supported graphics resolutions: 2592 x 1944 | Width: 110 mm | Power consumption (typical): 2.4 W | Number of cameras: 1 | Supported graphics resolutions: 1280 x 720 | Power consumption (max): 6.4 W | Angle of rotation: 270° | Height: 110 mm | Supported network protocols: IPv4 IPv6 HTTP TCP UDP ARP RTP RTSP RTCP RTMP SMTP FTP SFTP DHCP DNS DDNS QoS UPnP NTP Multicast ICMP IGMP NFS PPPoE P2P Bonjour Auto Registration | Depth: 110 mm | Operating relative humidity (H-H): 0 - 95% | Number of illumination LEDs: 2 | Form factor: Dome |

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

[www.shopro.lt](http://www.shopro.lt) | [info@shopro.lt](mailto:info@shopro.lt) | +370 693 39903

Supported graphics resolutions: 1920 x 1080 | Wide Dynamic Range (WDR): Yes | International Protection (IP) code: IP67 | Total megapixels: 8 MP | Operating temperature (T-T): -40 - 60 °C | Highlight Compensation (HLC): Yes | Ethernet LAN (RJ-45) ports: 1 | Night vision distance: 20 m | White balance: Manual | Housing material: Metal | Type: IP security camera | White balance: Natural | White balance: Street lamp | White balance: Auto | White balance: Regional custom | White balance: Outdoor | Mounting type: Ceiling/Wall/Pole | Mirror: Yes | Sensor type: CMOS | Progressive scan: Yes | Power consumption (Power over Ethernet (PoE)): 3 W | Video compression formats: MJPEG | Video compression formats: H.264 | Video compression formats: H.264H | Video compression formats: H.264B | Day/night mode: Yes | Video compression formats: H.265 | Night vision: Yes | Placement supported: Indoor & outdoor | Region of Interest (ROI) encoding: Yes | Noise reduction technology: 3D noise reduction | Camera shutter type: Mechanical | Camera shutter speed: 1/3 - 1/100000 s | Built-in HDD: No | Number of users: 20 user(s) | Management software: Smart PSS Lite DSS DMSS | Mobile operating systems supported: Android | Mobile operating systems supported: iOS | Camera shutter type: Auto | Video motion detection: Yes | Voice codecs: G.711Mu | Voice codecs: G.711a | Voice codecs: G.726 | Voice codecs: PCM | Number of Privacy masking areas: 4