



TP-Link Archer MR202 wireless router Fast Ethernet Dual- band (2.4 GHz 5 GHz) 4G Black



Modelis: MR202

Gamintojas: TP-LINK

EAN: 8885020625745

Prekės kodas: 540825

72.99€

Certification: CE, RoHS | Receiver sensitivity: 5 GHz: 11a 54M: -78 dBm 11ac VHT20: -92 dBm 11ac VHT20: -72 dBm 11ac VHT40: -90 dBm 11ac VHT40: -67 dBm 11ac VHT80: -87 dBm 11ac VHT80: -64 dBm 2,4 GHz: 11g 54M: -74 dBm 11n HT20: -91 dBm 11n HT20: -72 dBm 11n HT40: -88 dBm 11n HT40: -69 dBm | VPN support: PPTP VPN, OpenVPN | DHCP client: Yes | Product colour: Black | Stateful Packet Inspection (SPI): Yes | DC-in jack: Yes | Networking standards: IEEE 802.11g | Networking standards: IEEE 802.11n | Reset button: Yes | Ethernet LAN data rates: 10 | LED indicators: LAN, Power, WAN, WLAN | Networking standards: IEEE 802.11a | Web-based management: Yes | Networking standards: IEEE 802.11ac | Networking standards: IEEE 802.11b | Ethernet LAN data rates: 100 Mbit/s | AC adapter included: Yes | Storage temperature (T-T): -40 - 60 °C | 4G bands supported: 1800 | USB port: No | Wi-Fi standards: 802.11g | Width: 174 mm | 4G bands supported: 2100 | 4G bands supported: 800 | Cabling technology: 10/100Base-T(X) | Height: 33.5

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

mm | Antenna design: External | Quick installation guide: Yes | 4G bands supported: 2600 MHz | 4G bands supported: 850 | 4G bands supported: 2500 | Windows operating systems supported: Windows 7 | 4G standard: LTE-TDD & LTE-FDD | 4G bands supported: 700 | 4G bands supported: 2300 | Windows operating systems supported: Windows XP | UMTS bands supported: 2100 MHz | Mobile network generation: 4G | Quality of Service (QoS) support: Yes | Windows operating systems supported: Windows 8.1 | Windows operating systems supported: Windows Vista | UMTS bands supported: 850 | 4G: Yes | Output voltage: 12 V | 4G bands supported: 900 | Windows operating systems supported: Windows NT | Universal Plug and Play (UPnP): Yes | Static IP: Yes | Output current: 1 A | Operating relative humidity (H-H): 10 - 90% | Operating temperature (T-T): 0 - 40 °C | Guest access: Yes | Firewall: Yes | Windows operating systems supported: Windows 98SE | Wi-Fi standards: 802.11b | Dynamic IP: Yes | Cables included: LAN (RJ-45) | Wi-Fi standards: Wi-Fi 5 (802.11ac) | Windows operating systems supported: Windows 8 | Wi-Fi standards: 802.11a | Wi-Fi band: Dual-band (2.4 GHz / 5 GHz) | 3G: Yes | Antennas quantity: 2 | 3G standards: HSPA | Ethernet LAN: Yes | 3G standards: UMTS | WLAN data transfer rate (second band): 433 Mbit/s | SIM card slot: Yes | Plug and Play: Yes | WLAN data transfer rate (first band): 300 Mbit/s | Ethernet LAN (RJ-45) ports: 3 | Wi-Fi standards: Wi-Fi 4 (802.11n) | Firewall security: IP and MAC Address Binding | DHCP server: Yes | Port triggering: Yes | DMZ support: Yes | Transmit power: 20dBm(2.4G) 23dBm(5G) | Dynamic DNS (DDNS): Yes | Point-to-point protocol over Ethernet (PPPoE): Yes | Power source type: DC | Linux operating systems supported: Yes | DoS attack prevention: Yes | Top Wi-Fi standard: Wi-Fi 5 (802.11ac) | Ethernet WAN: Yes | Windows operating systems supported: Windows 2000 | Product type: Tabletop router | Depth: 124.5 mm | Mac operating systems supported: Yes | DSL WAN: No | UMTS bands supported: 900 | Ethernet LAN interface type: Fast Ethernet | Security algorithms: 128-bit WEP | Windows operating systems supported: Windows 10 | 3G/4G USB modem compatibility: No | Supported network protocols: IPv4, IPv6 | Port forwarding: Yes | WAN connection type: RJ-45 | Number of Ethernet LAN/WAN ports: 1 | Memory card slot(s): No | Warnings: Do not dismantle the unit yourself, there is a risk of electric shock. | Security algorithms: 64-bit WEP | Security algorithms: WPA2 | Browser supported: Internet Explorer 11, Firefox 12.0, Chrome 20.0, Safari 4.0 | Security algorithms: WPA2-PSK | Security algorithms: WPA-PSK | Storage relative humidity (H-H): 5 - 90% | WLAN data transfer rate (max): 733 Mbit/s | Warnings: Do not expose the device to extreme temperatures. | Security algorithms: WPA | Warnings: Do not expose the device to water or moisture.