



Digitus 2D Barcode Hand Scanner, Battery- Operated, Bluetooth & QR- Code Compatible

Modelis: DA-81003

Gamintojas: DIGITUS

EAN: 4016032473657

Prekės kodas: 540836

58.00€

Compatible operating systems: Mac | Linear (1D) barcodes supported: Code 128 | Linear (1D) barcodes supported: Code 93 | Linear (1D) barcodes supported: U.P.C. | Linear (1D) barcodes supported: Industrial 2 of 5 | Weight: 150 g | Linear (1D) barcodes supported: Codabar | Operating system installed: Linux | Product colour: Black | Maximum scan width: 10 cm | Operating temperature (T-T): -20 - 50 °C | Width: 63 mm | Battery technology: Lithium-Ion (Li-Ion) | Storage temperature (T-T): -40 - 70 °C | Linear (1D) barcodes supported: MSI | Linear (1D) barcodes supported: EAN-13 | Linear (1D) barcodes supported: EAN-8 | Linear (1D) barcodes supported: ITF-6 | Linear (1D) barcodes supported: ITF-14 | Linear (1D) barcodes supported: ISSN | Linear (1D)

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

barcodes supported: Code 32 | Linear (1D) barcodes supported: GS1-128 (UCC/EAN-128) | Country of origin: China | Harmonized System (HS) code: 84716070 | Standard interfaces: Bluetooth, RJ-45, USB | Mobile operating systems supported: iOS | Connectivity technology: Wired | Scanner type: 1D/2D | Read rate (max): 200 reads/s | Sensor type: CMOS | Input voltage: 5 V | Mobile operating systems supported: Android | Linear (1D) barcodes supported: Code 39 | Tilt reading angle: -60 - 60° | Height: 165 mm | Battery capacity: 2000 mAh | Windows operating systems supported: Yes | Battery type: Built-in battery | Cable length: 2 m | Depth: 87 mm | Linear (1D) barcodes supported: GS1 DataBar | International Protection (IP) code: IP54 | Power source type: Battery | Power consumption: 120 mA | Type: Handheld bar code reader | 2D (matrix & stacked) barcodes supported: QR Code | Light source: 650 nm | 2D (matrix & stacked) barcodes supported: Data Matrix | 2D (matrix & stacked) barcodes supported: PDF417 | Housing material: Acrylonitrile butadiene styrene (ABS) | Housing material: Polycarbonate (PC) | Linear (1D) barcodes supported: EAN 128 | Linear (1D) barcodes supported: IATA | Battery life: 18 h | Warnings: Avoid direct contact with eyes. | Warnings: Store away from sources of moisture. | Warnings: The appliance should be disposed of in accordance with local electro-waste regulations.