



ZyXel GS1200-5V3 Managed L2 Gigabit Ethernet (10/100/1000) Desktop Grey



Modelis: GS1200-5V3-EU0101F

Gamintojas: ZYXEL

EAN: 4718937649853

Prekės kodas: 540934

21.99€

Certification: CE-LVD, BSMI CE, EAC, FCC, BSMI Class B | AC input voltage: 100 - 240 V | AC input frequency: 50/60 Hz | Product colour: Grey | Networking standards: IEEE 802.1Q | Networking standards: IEEE 802.3x | Networking standards: IEEE 802.3u | Web-based management: Yes | Networking standards: IEEE 802.3az | Networking standards: IEEE 802.3ad | Networking standards: IEEE 802.3 | Networking standards: IEEE 802.3ab | Networking standards: IEEE 802.1p | Mean time between failures (MTBF): 1375342 h | Heat dissipation: 9.274 BTU/h | Jumbo frames: 15 | LED indicators: Yes | Broadcast storm control: Yes | Packet buffer memory: 0.192 MB | MAC address table: 4000 entries | Port mirroring: Yes | Form factor: Desktop | Switch type: Managed | Stackable: No | Multicast support: Yes | Operating relative humidity (H-H): 10 - 95% | Power supply included: Yes | VLAN support: Yes | Number of multicast groups filtered: 128 | Full duplex: Yes | Virtual LAN features: Port-based VLAN | Height: 26 mm | Depth: 75 mm | Fanless: Yes | Switch layer: L2 | Switching capacity: 10 Gbit/s | Copper ethernet cabling technology: 1000BASE-T | Jumbo frames support: Yes |

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

DHCP features: DHCP client | Power source: AC | Power connector: DC-in jack | Basic switching RJ-45 Ethernet ports quantity: 5 | Copper ethernet cabling technology: 10BASE-T | Copper ethernet cabling technology: 100BASE-T | Power consumption (max): 2.718 W | Weight: 172 g | Forwarding rate: 7.44 Mpps | IGMP snooping: Yes | Width: 121 mm | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | Rack mounting: No | Operating temperature (T-T): 0 - 50 °C | Flow control support: Yes | Queue scheduling algorithms: Weighted Round Robin (WRR) | 10G support: No | Password protection: Yes | Power over Ethernet (PoE): No | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Storage relative humidity (H-H): 10 - 95%