



CyberPower Tracer III VP1600ELCD-FR uninterruptible power supply (UPS) Line- Interactive 1.6 kVA 900 W 5 AC outlet(s)

Modelis: VP1600ELCD-FR

Gamintojas: CYBERPOWER

EAN: 4712856274912

Prekės kodas: 540954

264.99€

Serial interface: Yes | Operating altitude: 0 - 3048 m | Form factor: Tower | Waveform: Sine | AC outlets quantity: 5 AC outlet(s) | Automatic Voltage Regulation (AVR): Yes | UPS topology: Line-Interactive | Depth: 355 mm | Output power capacity: 1.6 kVA | Audible alarm modes: Alarm when on battery, Fault, Low battery alarm, Overload alarm | Input frequency: 50/60 Hz | Operating temperature (T-T): 0 - 40 °C | Serial ports quantity: 1 | Output frequency: 50/60 Hz | Maximum current: 6.96 A | Sustainability certificates: RoHS | USB port: Yes | Typical backup time at full load: 2

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

min | Ethernet LAN (RJ-45) ports: 1 | Manual: Yes | Surge protection: Yes | Display: LCD | Surge energy rating: 450 J | Typical backup time at half load: 11 min | Cables included: USB cable | Height: 281 mm | Audible alarm(s): Yes | Housing material: Plastic | USB port type: USB Type-B | Noise level: 40 dB | Storage relative humidity (H-H): 0 - 90% | Operating relative humidity (H-H): 0 - 90% | Serial interface type: RS-232 | Product colour: Black | Storage temperature (T-T): -20 - 50 °C | EMI/RFI noise filtering: Yes | Cable length: 1.5 m | Output power: 900 W | LED indicators: Yes | Response time: 4 ms | Input operation voltage (max): 295 V | Input operation voltage (min): 167 V | USB 2.0 ports quantity: 1 | Battery technology: Sealed Lead Acid (VRLA) | Width: 100 mm | Weight: 10.4 kg | Battery recharge time: 8 h | Non-operating altitude: 0 - 3048 m | Output operation voltage (max): 230 V