



TP-Link Omada AC1200 Wireless MU-MIMO Gigabit Wall- Plate Access Point



Modelis: EAP230-Wall

Gamintojas: TP-LINK

EAN: 1210002615679

Prekės kodas: 541000

72.99€

Compatible operating systems: Microsoft Windows XP, Vista, Windows 7, Windows 8, Windows10 | Quick start guide: Yes | LED indicators: Operation | 2.4 GHz: Yes | Ethernet LAN data rates: 1000 | Ethernet LAN data rates: 100 Mbit/s | Ethernet LAN data rates: 10 | Frequency band: 2.4 - 5 GHz | Product colour: White | Antenna type: Internal | Maximum data transfer rate: 1167 Mbit/s | 5 GHz: Yes | Security algorithms: WPA | Web-based management: Yes | MAC address filtering: Yes | Reset button: Yes | Networking standards: IEEE 802.11ac | Security algorithms: 152-bit WEP | Networking standards: IEEE 802.11b | MIMO: Yes | Security algorithms: WPA2-PSK | Security algorithms: WPA-PSK | Networking standards: IEEE 802.11g | Networking standards: IEEE 802.11n | Networking standards: IEEE 802.3at | Security algorithms: 64-bit WEP | Security algorithms: WPA2-Enterprise | Security algorithms: SNMPv2 | Networking standards: IEEE 802.3af | WAN connection: Ethernet (RJ-45) | Security algorithms: 128-bit WEP | Security algorithms: SNMP | Mounting kit: Yes | Package weight:

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

210 g | Operating temperature (T-T): 0 - 40 °C | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | Ethernet LAN (RJ-45) ports: 1 | Operating relative humidity (H-H): 10 - 90% | Power over Ethernet (PoE): Yes | Transmitting power (CE): 20 - 23 dBm | BeamForming: Yes | Sustainability compliance: Yes | 6 GHz: No | Compliance certificates: RoHS | Compliance certificates: CE | Package depth: 130 mm | Antenna features: Integrated antenna | MIMO type: Multi User MIMO | Virtual LAN features: Port-based VLAN | Automatic channel selection: Yes | Maximum data transfer rate (2.4 GHz): 300 Mbit/s | Width: 86.8 mm | Harmonized System (HS) code: 85176990 | Package width: 118 mm | Depth: 86.8 mm | VLAN support: Yes | Package height: 47 mm | Automatic channel scanning: Yes | Number of SSID supported: 16 | Antenna gain level (max): 3.6 dBi | Power consumption (typical): 9 W | Quantity per pack: 2 pc(s) | Height: 30.2 mm | Maximum data transfer rate (5 GHz): 867 Mbit/s | Storage relative humidity (H-H): 5 - 90% | Access Control List (ACL): Yes | Virtual LAN features: VLAN mapping | Syslog: Yes | Power consumption (max): 25.5 W | Cabling technology: 10/100/1000Base-T(X) | Wi-Fi Multimedia (WMM)/(WME): Yes | Service Set Identifier (SSID) features: Multiple SSIDs | Rate limiting: Yes | Placement: Wall | Antennas quantity: 2 | Band steering: Yes