



ASUS TUF- GAMING-750G- EVO power supply unit 750 W 20+4 pin ATX ATX Black



Modelis: 90YE00SB-B0NA00

Gamintojas: ASUS

EAN: 4711636287876

Prekės kodas: 541184

148.99€

PCI Express power connectors (16-pin): 1 | Total power: 750 W | Width: 140 mm | Package weight: 2.06 kg | Height: 86 mm | Cooling type: Active | Power protection features: Short circuit | Power protection features: Over voltage | Cables included: CPU, PCIe, Peripheral (Molex), SATA | Bearing technology: DBB | Illumination: No | 80 PLUS certification: 80 PLUS Gold | Mean time between failures (MTBF): 120000 h | Power protection features: Overheating | Power protection features: Over power | Weight: 1.32 kg | Package type: Box | Package width: 320 mm | Power protection features: Under voltage | Power protection features: Over current | Number of fans: 1 fan(s) | Power supply unit (PSU) form factor: ATX | Product colour: Black | Package height: 127 mm | Cabling type: Fully-Modular | Fan location: Top | Purpose: PC | ATX version: 3.1 | On/off switch: Yes | Package depth: 182 mm | AC input voltage: 100 - 240 V | PCI Express power connectors (6+2 pin): 2 | Peripheral (Molex) power connectors (4-pin): 2 | Depth: 150 mm | Number of SATA power connectors: 4 | CPU power connector

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

(4+4 pin): Yes | Max output current (+5V): 20 A | Combined power (+5Vsb): 15 W | PCI Express connector: Yes | Combined power (+5V): 110 W | Max output current (+5Vsb): 3 A | Combined power (-12V): 3.6 W | Max output current (-12V): 0.3 A | Motherboard power cable length: 50 cm | Peripheral (Molex) power cable length: 400 | Max output current (+3.3V): 20 A | Combined power (+12V): 750 W | Peripheral (Molex) power cable length: 120 | Combined power (+3.3V): 110 W | Max output current (+12V): 62.5 A | SATA power cable length: 400 | Motherboard power connector: 20+4 pin ATX | SATA power cable length: 120 | Power Factor Correction (PFC) type: Active