



ASUS PRIME H810M-A-CSM Intel H810 LGA 1851 (Socket V1) micro ATX motherboard

Modelis: 90MB1KK0-M0EAYC

Gamintojas: ASUS

EAN: 4711387844625

Prekės kodas: 541202

130.99€

DisplayPort version: 1.4 | Audio output channels: 7.1 channels | CPU fan connector: Yes |
Motherboard chipset family: Intel | USB 3.2 Gen 1 (3.1 Gen 1) connectors: 2 | Maximum internal
memory: 128 GB | Front panel audio connector: Yes | Package weight: 782 g | BIOS type: UEFI AMI |
Product colour: Black | Supported storage drive interfaces: M.2, PCI Express 4.0, SATA III | S/PDIF out
connector: Yes | USB 2.0 connectors: 1 | Unbuffered memory: Yes | LAN controller: Intel I219V | USB
2.0 ports quantity: 4 | Number of M.2 (M) slots: 2 | Motherboard form factor: micro ATX | Weight: 534
g | Number of SATA III connectors: 4 | Wake-on-LAN ready: Yes | Supported storage drive types: HDD
& SSD | DisplayPorts quantity: 1 | EPS power connector (8-pin): Yes | Windows operating systems
supported: Windows 10 x64 | Supported processor sockets: LGA 1851 | Motherboard chipset: Intel
H810 | Ethernet LAN (RJ-45) ports: 1 | Number of COM connectors: 1 | Package width: 270 mm |
Number of chassis fan connectors: 2 | Windows operating systems supported: Windows 11 | Parallel

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be
išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

processing technology support: Not supported | Front panel connector: Yes | Power source type: ATX | ATX Power connector (24-pin): Yes | Supported memory clock speed (max): 6400 MHz | Ethernet LAN: Yes | Package depth: 263 mm | HDMI version: 2.1 | USB 3.2 Gen 2 (3.1 Gen 2) Type-A ports quantity: 2 | Depth: 222 mm | TPM connector: Yes | Processor manufacturer: Intel | Compatible processor series: Intel Core Ultra (Series 2) | PCI Express x1 (Gen 4.x) slots: 1 | Width: 244 mm | Number of HDDs supported: 4 | HDMI ports quantity: 1 | PCI Express x16 (Gen 4.x) slots: 1 | RGB LED pin header: Yes | Line-in: Yes | Number of M.2 (E) slots: 1 | Memory slots type: DIMM | On-board graphics card: No | Microphone in: Yes | Package height: 51.5 mm | Supported memory types: DDR5-SDRAM | Number of memory slots: 2 | PS/2 ports quantity: 1 | Memory channels: Dual-channel | Wi-Fi: No | Height: 37 mm | Processor socket: LGA 1851 (Socket V1) | Ethernet interface type: Gigabit Ethernet | Number of storage drives supported: 6 | 1st M.2 highest PCI Express generation: 4.0 | 2nd M.2 largest key size: 2280 | Number of CPU fan connectors: 1 | Number of RGB LED pin headers: 3 | 1st M.2 largest key size: 2280 | Warnings: In case of installation problems, contact a qualified service technician. | ECC compatibility: Non-ECC | 2nd M.2 highest PCI Express generation: 4.0 | Warnings: Do not open or modify the motherboard to prevent damage. | Warnings: When disposing of the product, follow local regulations for the recycling of electronics. | Number of EPS power connectors (8-pin): 1