



TP-Link Omada EAP225 wireless access point 1350 Mbit/s White Power over Ethernet (PoE)



Modelis: EAP225

Gamintojas: TP-LINK

EAN: 1210002618496

Prekės kodas: 541210

83.99€

Compatible operating systems: Microsoft Windows XP, Vista, Windows 7, Windows 8, Windows10, Linux | Airtime Fairness (ATF): Yes | Service Set Identifier (SSID) features: Multiple SSIDs | PoE adapter included: Yes | Transmitting power (CE): 23 dBm | SIM card slot: No | 6 GHz: No | Syslog: Yes | Virtual LAN features: VLAN mapping | Band steering: Yes | Transmitting power (FCC): 24 dBm | Power over Ethernet (PoE) type supported: Passive PoE | BeamForming: Yes | Sustainability compliance: Yes | Compliance certificates: RoHS | Compliance certificates: CE | Compliance certificates: Federal Communications Commission (FCC) | On/off switch: Yes | Antenna features: Integrated antenna | DC-in jack: Yes | Package weight: 910 g | Operating temperature (T-T): 0 - 40 °C | 2.4 GHz: Yes | Operating relative humidity (H-H): 10 - 90% | Cable lock slot type: Kensington |

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

Maximum data transfer rate (2.4 GHz): 450 Mbit/s | Web-based management: Yes | MAC address filtering: Yes | Networking standards: IEEE 802.11ac | Security algorithms: 128-bit WEP | Height: 37.1 mm | MIMO: Yes | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | Package type: Box | Product colour: White | AC adapter included: Yes | Mounting kit: Yes | Antenna direction type: Omni-directional | VLAN support: Yes | MIMO type: Multi User MIMO | Package depth: 340 mm | Package height: 65 mm | Ethernet LAN (RJ-45) ports: 1 | Number of SSID supported: 16 | Networking standards: IEEE 802.11b | LED indicators: Power | Maximum data transfer rate (5 GHz): 867 Mbit/s | Cable lock slot: Yes | Wi-Fi Multimedia (WMM)/(WME): Yes | Quantity per pack: 1 pc(s) | Antenna gain level (max): 5 dBi | Output voltage: 12 V | Package width: 228 mm | Maximum data transfer rate: 1350 Mbit/s | Harmonized System (HS) code: 85176990 | Security algorithms: WPA-PSK | Storage relative humidity (H-H): 5 - 90% | Power consumption (typical): 10.15 W | Output current: 1.5 A | Reset button: Yes | Ethernet LAN data rates: 10 | Depth: 181.5 mm | Ethernet LAN data rates: 100 Mbit/s | Rate limiting: Yes | Antenna type: Internal | Access Control List (ACL): Yes | Networking standards: IEEE 802.3af | Security algorithms: WPA | Security algorithms: 152-bit WEP | Placement: Ceiling, Wall | Networking standards: IEEE 802.11a | Networking standards: IEEE 802.11g | Networking standards: IEEE 802.11n | Power over Ethernet (PoE): Yes | Security algorithms: 64-bit WEP | Security algorithms: WPA2 | Security algorithms: WPA2-PSK | 5 GHz: Yes | LED indicators: WLAN | Security algorithms: SSID | Antennas quantity: 5 | Quick start guide: Yes | Width: 205.5 mm | Cabling technology: 10/100/1000Base-T(X) | Ethernet LAN data rates: 1000