



TP-Link EAP720 wireless access point 4324 Mbit/s White Power over Ethernet (PoE)



Modelis: EAP720

Gamintojas: TP-LINK

EAN: 1210002608732

Prekės kodas: 541385

118.99€

Depth: 160 mm | Access Control List (ACL): Yes | Channel bandwidth: 240 MHz | Supported network protocols: IPv4/IPv6 | VLAN support: Yes | Maximum data transfer rate (2.4 GHz): 688 Mbit/s | Rate limiting: Yes | Syslog: Yes | Guest access: Yes | Placement: Ceiling, Wall | Package height: 65 mm | Wi-Fi Multimedia (WMM)/(WME): Yes | Height: 36.7 mm | Remote Authentication Dial-In User Service (RADIUS): Yes | BeamForming: Yes | Access point management: Wi-Fi schedule | Width: 160 mm | Maximum data transfer rate (5 GHz): 4324 Mbit/s | Flash memory: 128 MB | Maximum Tx power (2.4 GHz): 25 dBmW | DC voltage range: 12 V | Power over Ethernet (PoE) type supported: PoE+ | 6 GHz: No | Maximum Tx power (5 GHz): 25 dBmW | Airtime Fairness (ATF): Yes | Schedule access: Yes | Cloud-managed: Yes | Internal memory: 4096 MB | Package depth: 228 mm | Reset button: Yes | Package width: 245 mm | Mounting kit: Yes | Package weight: 792 g | Operating temperature (T-T): 0 - 40 °C | Input current: 1.5 A | LED indicators: Yes | DHCP client: Yes | Networking standards: IEEE

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

802.1x | Networking standards: IEEE 802.3bz | Security algorithms: WPA-Personal | Storage relative humidity (H-H): 5 - 90% | Antenna type: Internal | DC-in jack: Yes | Maximum data transfer rate: 4324 Mbit/s | Security algorithms: SNMP | Security algorithms: SSID | Security algorithms: WPA3-Enterprise | Networking standards: IEEE 802.11e | Networking standards: IEEE 802.11g | Networking standards: IEEE 802.11n | Security algorithms: EAP-TLS | Security algorithms: EAP-GTC | Security algorithms: PPSK | Quick start guide: Yes | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | Web-based management: Yes | MAC address filtering: Yes | Security algorithms: EAP-PEAP | 2.4 GHz: Yes | Networking standards: IEEE 802.11a | Networking standards: IEEE 802.3ab | Security algorithms: EAP-AKA | Spread spectrum method: OFDMA | Weight: 410 g | Power consumption (max): 17.83 W | Ethernet LAN data rates: 2500 Mbit/s | Ethernet LAN (RJ-45) ports: 1 | Networking standards: IEEE 802.1Q | Networking standards: IEEE 802.3x | Networking standards: IEEE 802.11ax | Security algorithms: WPA3-Personal | Security algorithms: SSH | Security algorithms: WPA-Enterprise | Networking standards: IEEE 802.3at | Networking standards: IEEE 802.11v | Security algorithms: EAP-TTLS | Security algorithms: WPA2-Personal | Networking standards: IEEE 802.11r | Security algorithms: EAP-FAST | Product colour: White | Networking standards: IEEE 802.11be | Security algorithms: WPA2-Enterprise | Security algorithms: SNMPv2 | Operating relative humidity (H-H): 10 - 90% | AC adapter included: Yes | Firmware upgradeable: Yes | Networking standards: IEEE 802.11ac | Security algorithms: SNMPv3 | Networking standards: IEEE 802.11k | Security algorithms: EAP-MD5 | 5 GHz: Yes | Power over Ethernet (PoE): Yes | Networking standards: IEEE 802.11i | Networking standards: IEEE 802.11b | Security algorithms: PEAP | Security algorithms: EAP-SIM | Compliance certificates: RoHS | Compliance certificates: CE | Compliance certificates: Federal Communications Commission (FCC) | Compliance certificates: Industry Canada (IC) | Coverage area: 140 m²