



ASRock B860M Pro-A WiFi Motherboard



Modelis: B860M Pro-A WiFi

Gamintojas: ASROCK

EAN: 4711581490307

Prekės kodas: 541426

134.00€

Certification: FCC, CE, ErP/EuP | RAID support: Yes | USB connector type: USB Type-C | Ethernet LAN (RJ-45) ports: 1 | BIOS type: UEFI AMI | CPU fan connector: Yes | Number of M.2 (M) slots: 3 | Ethernet LAN data rates: 10,100,1000,2500 Mbit/s | Audio chip: Realtek ALC897 | TPM connector: Yes | Number of SATA III connectors: 4 | Number of SATA III connectors: 4 | USB connector type: USB Type-A | ATX Power connector (24-pin): Yes | Supported processor sockets: LGA 1851 | Bluetooth: Yes | Motherboard form factor: micro ATX | Motherboard chipset family: Intel | Wi-Fi: Yes | Number of chassis fan connectors: 3 | Supported storage drive interfaces: M.2, PCI Express 4.0, SATA III | RAID levels: 5 | Maximum internal memory: 256 GB | Motherboard chipset: Intel B860 | RAID levels: 10 | Supported storage drive types: HDD & SSD | Antennas quantity: 2 | USB 2.0 connectors: 2 | Unbuffered memory: Yes | Windows operating systems supported: Windows 11 x64 | RAID levels: 1 | Memory channels: Dual-channel | RAID levels: 0 | Width: 244 mm | Audio output channels: 7.1 channels | LAN controller: Dragon RTL8125BG | Processor manufacturer: Intel | USB 2.0 ports quantity: 2 | USB 3.2 Gen 1 (3.1 Gen 1) connectors: 1 | HDMI version: 2.1 | HDMI ports quantity: 2 | Number of CPU fan connectors: 2 | Flashback BIOS button: Yes | 1st M.2 largest key size: 2280 | ECC compatibility: Non-ECC | Warnings: Do not open or modify the motherboard to prevent damage. |

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

Warnings: In case of installation problems, contact a qualified service technician. | Warnings: When disposing of the product, follow local regulations for the recycling of electronics. | 1st M.2 highest PCI Express generation: 5.0 | Number of water pump connectors: 1 | Number of USB 3.2 Gen 1 ports: 3 | Ethernet LAN: Yes | Number of memory slots: 4 | 12V power connector: Yes | Supported memory types: DDR5-SDRAM | USB 3.2 Gen 1 (3.1 Gen 1) Type-C ports quantity: 1 | Processor socket: LGA 1851 (Socket V1) | RGB LED pin header: Yes | Memory slots type: DIMM | Depth: 244 mm | Ethernet interface type: 2.5 Gigabit Ethernet