



Qoltec 53772 uninterruptible power supply (UPS) Line- Interactive 0.65 kVA 360 W 1 AC outlet(s)



Modelis: 53772

Gamintojas: QOLTEC

EAN: 5901878537726

Prekės kodas: 541449

79.99€

Overvoltage protection: Y | Warnings: Keep away from sources of fire and water. | Warnings: Use the appliance in well-ventilated areas to avoid overheating. | Warnings: Do not disassemble the unit housing, there may be a risk of electric shock. | Operating temperature (T-T): 0 - 40 °C | Cold start: Yes | Automatic Voltage Regulation (AVR): Yes | AC outlet types: Type E | Output power capacity: 0.65 kVA | AC outlet types: C13 coupler | AC outlets quantity: 1 AC outlet(s) | UPS topology: Line-Interactive | AC outlet types: Type F | Depth: 275 mm | Battery voltage: 12 V | Power factor: 0.6 | Power protection features: Overload | Power protection features: Under voltage | Power protection features: Short circuit | Power protection features: Over voltage | Typical backup time at full load: 14 min | LED indicators: Power | Product colour: Black | Width: 90 mm | Input operation voltage (max):

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

300 V | Package width: 325 mm | Output operation voltage (min): 220 V | Input frequency: 50/60 Hz |
Output power: 360 W | LED indicators: Signal strength | Input operation voltage (min): 140 V |
Height: 140 mm | Battery capacity: 7 Ah | Manual: Yes | Waveform: Sine | Storage temperature (T-T):
-15 - 45 °C | Noise level: 40 dB | Weight: 4.8 kg | Package height: 221 mm | Battery recharge time: 6
h | Output operation voltage (max): 230 V | Storage relative humidity (H-H): 0 - 90%