



TP-Link Omada 48-Port Gigabit L2+ Managed Switch with 4 SFP Slots



Modelis: TL-SG3452

Gamintojas: TP-LINK

EAN: 1210002611923

Prekės kodas: 541670

398.99€

Certification: CE, FCC, RoHS | Quick start guide: Yes | Package height: 100 mm | Networking standards: IEEE 802.1D | Networking standards: IEEE 802.3z | Operating temperature (T-T): 0 - 40 °C | Power consumption (max): 34.86 W | Switching capacity: 104 Gbit/s | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Height: 44 mm | Access Control List (ACL): Yes | Networking standards: IEEE 802.3u | Networking standards: IEEE 802.1w | Heat dissipation: 118.94 BTU/h | Switch type: Managed | AC input voltage: 100 - 240 V | Web-based management: Yes | MAC address filtering: Yes | Networking standards: IEEE 802.3ab | Networking standards: IEEE 802.1p | Package width: 528 mm | DHCP features: DHCP snooping | Switch layer: L2 | Form factor: 1U | AC input frequency: 50/60 Hz | DHCP features: DHCP server | Networking standards: IEEE 802.3i | DHCP features: DHCP client | DHCP features: DHCP relay | Operating relative humidity (H-H): 10 - 90% | Power supply included: Yes | Storage relative humidity (H-H): 5 - 90% | Cables included: AC | DHCP features: DHCPv6 snooping | Package weight: 4.26 kg | Rack mounting: Yes | Harmonized System

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

(HS) code: 85176990 | IGMP snooping: Yes | Networking standards: IEEE 802.1s | Power over Ethernet (PoE): No | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | Depth: 220 mm | SFP module slots quantity: 4 | Number of VLANs: 4000 | Product colour: Black | Width: 440 mm | Internal memory: 256 MB | Port mirroring: Yes | MAC address table: 16000 entries | Flash memory: 32 MB | Package depth: 336 mm | VLAN support: Yes | Power source: AC | Multicast support: Yes | 10G support: No | Ethernet LAN data rates: 10,100,1000 Mbit/s | Basic switching RJ-45 Ethernet ports quantity: 48 | Jumbo frames support: Yes | IPv4 routes: 48 | Store-and-forward: Yes | Policy-based routing: Yes | ARP inspection: Yes | Broadcast storm control: Yes | Multicast Listener Discovery (MLD) snooping: Y | BPDU filtering/protection: Yes | Fanless: Yes | Configuring Location Settings (CLI): Yes | Link aggregation: Yes | Spanning tree protocol: Yes | Gigabit Ethernet (copper) ports quantity: 48 | Jumbo frames: 9000 | System event log: Yes | IPv4 & IPv6 features: IPv4/IPv6 access-control list (ACL) | Console port: RJ-45/micro-USB | Cloud-managed: Yes | IPv4 & IPv6 features: IPv6 ping | IPv4 & IPv6 features: IPv6 Telnet | IP-MAC-Port binding: Yes | Authentication: MAC-based authentication, Port-based authentication | Static route: Yes | Virtual LAN features: Voice VLAN | Management protocols: SNMPv1/v2c/v3, SNTP | Virtual LAN features: Tagged VLAN | Head-of-line (HOL) blocking: Yes | Authentication type: AAA, RADIUS, TACACS+ | Virtual LAN features: Protocol-based VLAN | Virtual LAN features: Port-based VLAN | IPv4 & IPv6 features: IPv6 tracert | Virtual LAN features: Private VLAN | GARP VLAN Registration Protocol (GVRP): Yes | Rack mount kit: Yes | SSH/SSL support: Yes | Flow control support: Yes | IPv6 routes: 48 | Loop protection: Yes | IP routing: Yes | Forwarding rate: 77.4 Mpps | MIB support: Yes