

TP-Link Omada 48-Port Gigabit L2+ Managed Switch with 4 SFP Slots

Gamintojas: **TP-LINK** · Modelis: **TL-SG3452** · EAN: **1210002611923** · Prekės kodas: **541670**



392,90 €

Kaina su PVM

Be PVM: **324,71 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt



Aprašymas

Certification: CE, FCC, RoHS | Networking standards: IEEE 802.3ab | Networking standards: IEEE 802.1p | Networking standards: IEEE 802.3i | Networking standards: IEEE 802.3u | SFP module slots quantity: 4 | Networking standards: IEEE 802.1D | Networking standards: IEEE 802.3z | Web-based management: Yes | MAC address filtering: Yes | Networking standards: IEEE 802.1s | AC input frequency: 50/60 Hz | Operating temperature (T-T): 0 - 40 °C | DHCP features: DHCPv6 snooping | DHCP features: DHCP server | Form factor: 1U | DHCP features: DHCP client | DHCP features: DHCP relay | Package weight: 4.26 kg | Package width: 528 mm | DHCP features: DHCP snooping | Switch layer: L2 | Access Control List (ACL): Yes | Networking standards: IEEE 802.1w | Flash memory: 32 MB | Operating relative humidity (H-H): 10 - 90% | Heat dissipation: 118.94 BTU/h | VLAN support: Yes | Switch type: Managed | Depth: 220 mm | Multicast support: Yes | Package height: 100 mm | Rack mounting: Yes | MAC address table: 16000 entries | Power over Ethernet (PoE): No | Width: 440 mm | Basic switching RJ-45 Ethernet ports quantity: 48 | Height: 44 mm | Harmonized System (HS) code: 85176990 | IGMP snooping: Yes | Package depth: 336 mm | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | Power consumption (max): 34.86 W | Product colour: Black | Internal memory: 256 MB | 10G support: No | Cables included: AC | Quick start guide: Yes | Switching capacity: 104 Gbit/s | Number of VLANs: 4000 | Port mirroring: Yes | Storage relative humidity (H-H): 5 - 90% | AC input voltage: 100 - 240 V | Power supply included: Yes | Jumbo frames support: Yes | Power source: AC | Ethernet LAN data rates: 10,100,1000 Mbit/s | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | IPv4 & IPv6 features: IPv6 Telnet | Forwarding rate: 77.4 Mpps | BPDU filtering/protection: Yes | IPv4 & IPv6 features: IPv6 tracer | Virtual LAN features: Protocol-based VLAN | Virtual LAN features: Tagged VLAN | Virtual LAN features: Port-based VLAN | Store-and-forward: Yes | IP-MAC-Port binding: Yes | Static route: Yes | Authentication type: AAA, RADIUS, TACACS+ | IPv4 & IPv6 features: IPv6 ping | Policy-based routing: Yes | Spanning tree protocol: Yes | Gigabit Ethernet (copper) ports quantity: 48 | Jumbo frames: 9000 | Loop protection: Yes | Virtual LAN features: Private VLAN | Fanless: Yes | Head-of-line (HOL) blocking: Yes | Broadcast storm control: Yes | Multicast Listener Discovery (MLD) snooping: Y | System event log: Yes | Console port: RJ-45/micro-USB | Management protocols:

SNMPv1/v2c/v3, SNTP | Configuring Location Settings (CLI): Yes | Link aggregation: Yes | ARP inspection: Yes | MIB support: Yes | GARP VLAN Registration Protocol (GVRP): Yes | Cloud-managed: Yes | IPv4 & IPv6 features: IPv4/IPv6 access-control list (ACL) | IP routing: Yes | Virtual LAN features: Voice VLAN | Rack mount kit: Yes | Authentication: MAC-based authentication, Port-based authentication | SSH/SSL support: Yes | Flow control support: Yes | IPv4 routes: 48 | IPv6 routes: 48

Techninė specifikacija

Specifications	
Sandėlio grupė	Switches [+83][-71]
Matmenys ir svoris	
Matmenys (I × P × A)	34,00cm × 10,00cm × 53,00cm
Svoris	4,70kg