



Zebra DS2208 Handheld bar code reader 1D/2D LED Black



Modelis: DS2208-SR7U2100SGW

Gamintojas: ZEBRA

EAN:

Prekės kodas: 541713

93.99€

Linear (1D) barcodes supported: GS1 DataBar Expanded | Motion tolerance (cm/s): 13 | Linear (1D) barcodes supported: Code 128 | Linear (1D) barcodes supported: Codabar | Depth: 99 mm | Linear (1D) barcodes supported: Code 11 | Linear (1D) barcodes supported: EAN-13 | Linear (1D) barcodes supported: MSI | Linear (1D) barcodes supported: Code 39 | Linear (1D) barcodes supported: Interleaved 2 of 5 | Connectivity technology: Wired | Scanner type: 1D/2D | Product colour: Black | Sensor type: LED | Linear (1D) barcodes supported: Code 93 | Linear (1D) barcodes supported: U.P.C. | Wavelength: 645 nm | Width: 66 mm | Charging base: No | Tilt reading angle: -65 - 65° | Operating relative humidity (H-H): 5 - 95% | Standard interfaces: USB, RS-232, RS-485, Keyboard wedge | Storage temperature (T-T): -40 - 70 °C | 2D (matrix & stacked) barcodes supported: MaxiCode | Optical sensor resolution (W x H): 640 x 480 pixels | Pitch reading angle: -65 - 65° | Working distance: 36.8 cm | 2D (matrix & stacked) barcodes supported: Micro QR Code | International Protection (IP) code: IP42 | 2D (matrix & stacked) barcodes supported: PDF417 | Weight: 161.6 g | 2D (matrix & stacked) barcodes supported: QR Code | Operating temperature (T-T): 0 - 50 °C | 2D (matrix & stacked) barcodes supported: TLC-39 | 2D (matrix & stacked) barcodes supported:

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

Composite Codes | 2D (matrix & stacked) barcodes supported: Data Matrix | Type: Handheld bar code reader | 2D (matrix & stacked) barcodes supported: Han Xin | 2D (matrix & stacked) barcodes supported: Aztec Code | Cables included: Micro-USB | Sustainability certificates: RoHS | Height: 165 mm | LED indicators: Yes | Yaw reading angle: -65 - 65°