

Zebra DS3678-SR Rankinis brūkšninių kodų skaitytuvas 1D/2D LED Juoda, Žalia

Gamintojas: ZEBRA · Modelis: DS3678-SR3U42A0SFW · EAN: · Prekės kodas: 541715



588,89 €

Kaina su PVM

Be PVM: 486,69 €

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Rankinis brūkšninių kodų skaitytuvas Juoda, Žalia
- ✓ Skenerio tipas: 1D/2D Jutiklio tipas: LED
- ✓ Codabar, Code 11, Code 128, Code 39, Code 93, GS1-128 (UCC/EAN-128), MSI, Plessey, U.P.C. Aztec Code, Sudėtiniai kodai, Duomenų matrica, Han Xin, MaxiCode, Micro QR Code, MicroPDF417, PDF417, QR Code, TLC-39
- ✓ Polinkio skaitymo kampas: -65 - 65°
- ✓ Vielinis ir Bevielis Standartinės sąsajos: RS-232, USB, Klaviatūros prijungimas
- ✓ Nedaug energijos naudojantis „Bluetooth“ (BLE)
- ✓ Maitinimo šaltinio tipas: Baterija Ličio-jonų (Li-Ion) 3100 mAh



Aprašymas

Unstoppable performance for standard range 1D/2D barcode capture

The productivity of your warehouse and manufacturing workers depends on the quality of their scanners. The DS3600-SR Ultra-Rugged scanner enables reliable capture of 1D and 2D barcodes at standard ranges—from near contact to nearly 5 ft./1.5 m away. Built for your toughest environments, the DS3600-SR is virtually indestructible, including an enhanced 10 ft./3 m drop spec to concrete and dual IP65/IP68 sealing. With

DataCapture DNA, Zebra's exclusive software ecosystem, you can take scanner performance far beyond the basics—simplifying every stage of the scanning experience over the life of your device. And when it comes to cordless technology, the DS3678-SR's Zebra-only features put it in a class of its own. The DS3600-SR—the unstoppable performance you need to maximize workforce productivity and throughput in your operations.

Performs In Your Toughest Environments

Scan it All—at Astonishing Speeds

Workers can capture virtually any 1D or 2D barcode as fast as they can pull the trigger, whether they're in hand or as far as 5 ft./1.5 m away—faster and farther than other standard range scanners. Powered by Zebra's exclusive PRZM Intelligent Imaging technology and the highest sensor resolution in its class, the DS3600-SR instantly captures the most problematic barcodes—including barcodes that are dirty, damaged, poorly printed and under shrinkwrap.

Ultra-Rugged—the Most Indestructible Design in its Class

Zebra ultra-rugged scanners earned their name for a reason—you won't find a tougher family of scanners. Ready for the world's harshest environments, the DS3600-SR has the highest drop, tumble and sealing specifications in its class. It can survive 10 ft./3 m drops to concrete and 7,500 tumbles. With dual IP65/IP68 sealing, the DS3600-SR is dust proof, can handle the force of jetting water and be fully submerged in water. Built to withstand extreme heat, cold and humidity, the DS3600-SR can be used anywhere— indoor, outdoor and even in the freezer.

Ultra-Rugged Cradle and Charging Contacts Designed to Last

The DS3600-SR is the first scanner in its class to offer a cradle with IP65 sealing. Its industrial charging contacts withstand 250,000 insertions. And Zebra's exclusive Connect+ Contact technology assures reliable, corrosion-free charging over the life of the scanner.

Easily Capture Label Data for Better Inventory Management

With Label Parse+, the DS3600-SR can instantly capture and parse GS1 label barcode data on items, enabling workers to easily capture a wealth of data, including expiration dates and lot number/manufacturing location.

Read Up To 20 Barcodes with One Press of the Scan Trigger

With Multi-Code Data Formatting (MDF), the DS3600-SR can capture multiple barcodes with a single scan and transmit only the barcodes you need, in the order your application expects.

Faster Pick-List Processing

Users can easily select and capture an individual barcode from any pick list.

Flexible Feedback Modes

Mix and match the feedback modes that best fit your environment—vibration, wraparound LEDs that are easy to see from any position, a beep tone and Zebra's Direct Decode Indicator that projects illumination on the captured barcode.

Support for the Barcode of the Future—Digimarc™

DS3600-SR scanners support Digimarc digital watermark technology, where barcodes are printed repeatedly over all surfaces yet are invisible to workers and consumers. Digimarc saves time at checkout and also creates efficiencies throughout the supply chain since workers no longer need to locate and position a visible barcode in the field of view.

Superior Cordless Technology

More Than 100,000 Scans on a Single Charge

The PowerPrecision+ battery delivers the ultimate in battery power and management. You get more than twice the amount of scans per charge than with competitive models, so workers can scan more items over a longer period of time. You also get visibility into a wealth of battery health-related data, including charge cycles consumed, current battery status and a State of Health meter, which identifies if batteries are healthy and holding a full charge, no longer holding a full charge, or at end of life and require replacement.

Battery and Bluetooth™ Status At-A-Glance

The first-in-its-class battery 'charge gauge' and Bluetooth status LED make it easy to monitor battery power as well as Bluetooth connectivity.

Switch Workflows in an Instant with AutoConfig

Since scanner settings are stored in the cradle base, simply pair the DS3600-SR to a different base to automatically configure it for a new host application. For example, you can take a scanner from the forklift and use it for shipping without manually changing settings.

Keep Track of Your Scanners and Prevent Workflow Interruptions

With Virtual Tether, you won't have to worry about a warehouse worker leaving a scanner behind on a pallet. Both the scanner and cradle will alert users when a scanner is taken beyond its Bluetooth range or left out of the cradle for a predefined length of time.

Eliminate Bluetooth interference with Wi-Fi Friendly Mode

Zebra's exclusive Wi-Fi Friendly Mode eliminates the wireless interference that Bluetooth devices can create in your Wi-Fi environment.

Unrivalled Manageability

Instantly Connect to Your Industrial Ethernet Network

Zebra's Network Connect for Automation delivers a seamless connection between DS3600-SR scanners and a manufacturer's Industrial Ethernet network without the need for third party conversion equipment. The solution eliminates vulnerability points, improves security, reduces complexity and is compatible with every Zebra 3600 Series scanner.

Identify and Correct Problem Barcodes with ScanSpeed Analytics

Only from Zebra, ScanSpeed Analytics provides detailed metrics on every barcode captured—enabling you to identify poor performing barcodes that slow down your operations.

No-Cost Tools to Meet Your Management Needs

With 123Scan, you can easily create configuration barcodes to program scanners. If your imagers are in multiple locations across the country or around the world, with Scanner Management Service (SMS), you can configure and update the firmware for any DS3600-SR device that is plugged into the host—no depot staging or user action is required.

Up-To-The-Minute Insight Into Every Aspect of Your Scanners

The logging agent's Remote Diagnostics capabilities automate the recording of scanner asset information, health and statistics, configuration settings and barcode data—giving you the information needed for event verification, blockchain traceability, pilot site ROI generation, troubleshooting and predictive fleet-wide trend analysis.

Techninė specifikacija

Nuskaitymas

Tipas

Rankinis brūkšnių kodų skaitytuvas

Skenerio tipas	1D/2D
Jutiklio tipas	LED
Palaikomi linijiniai (1D) brūkšniniai kodai	Codabar, Code 11, Code 128, Code 39, Code 93, GS1-128 (UCC/EAN-128), MSI, Plessey, U.P.C.
Palaikomi 2D (matricos ir sudėtiniai) brūkšniniai kodai	Aztec Code, Sudėtiniai kodai, Duomenų matrica, Han Xin, MaxiCode, Micro QR Code, MicroPDF417, PDF417, QR Code, TLC-39
Bangos ilgis	610 nm
Polinkio skaitymo kampas	-65 - 65°
Pitch skaitymo kampas	-65 - 65°
Pokrypio skaitymo kampas	-45 - 45°
Optinių jutiklių rezoliucija	1280 pikseliai
Ryšys	
Ryšio technologija	Vielinis ir Bevielis
Standartinės sąsajos	RS-232, USB, Klaviatūros prijungimas
Belaidžio ryšio atstumas	100 m
Bluetooth versija	4.0
Nedaug energijos naudojantis „Bluetooth“ (BLE)	Taip
Ethernet LAN jungtis	Taip
Veikimo charakteristikos	
Produkto spalva	Juoda, Žalia
Tarptautinės apsaugos (IP) kodas	IP67
Apsaugos ypatybės	Atsparus dulkėms, Atsparus smūgiams, Atsparus vandeniui
LED indikatoriai	Taip
Programavimo funkcija	Taip
Energijos valdymas	
Maitinimo šaltinio tipas	Baterija
Nuskaitymo skaičius per mokestį	100000
Svoris ir matmenys	
Svoris	407 g
Plotis	142 mm
Ilgis	76 mm
Aukštis	185 mm
Aplinkos sąlygos	
Darbo temperatūros diapazonas (TT)	-20 - 50 °C
Sandėliavimo temperatūros norma (T-T)	-40 - 70 °C

Darbo santykinės drėgmės diapazonas	5 - 95%
Baterija	
Baterijos technologija	Ličio-jonų (Li-Ion)
Baterijos talpa	3100 mAh
Techninė informacija	
Atitikties sertifikatai	RoHS
Logistikos duomenys	
Darniosios sistemos (DS) kodas	84716070
Matmenys ir svoris	
Matmenys (I × P × A)	32,00cm × 17,00cm × 27,00cm
Svoris	1,75kg

Dokumentai ir vaizdo įrašai

› [Gaminio lankstinukas](#)

Gamintojo ir saugos informacija

GAMINTOJAS

Zebra

ATSAKINGAS ASMUO ES

Zebra Technologies

Borupvang 3, Ballerup, DK
zebra.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt