



Zebra DS3678-SR Handheld bar code reader 1D/2D LED Black, Green



Modelis: DS3678-SR3U42A0SFW

Gamintojas: ZEBRA

EAN:

Prekės kodas: 541715

600.99€

Battery technology: Lithium-Ion (Li-Ion) | Programming function: Yes | Ethernet LAN: Yes | Width: 142 mm | Operating relative humidity (H-H): 5 - 95% | Product colour: Green | International Protection (IP) code: IP67 | Harmonized System (HS) code: 84716070 | Battery capacity: 3100 mAh | Standard interfaces: RS-232, USB, Keyboard wedge | LED indicators: Yes | Operating temperature (T-T): -20 - 50 °C | Bluetooth version: 4.0 | Wavelength: 610 nm | Height: 185 mm | Tilt reading angle: -65 - 65° | Product colour: Black | Weight: 407 g | Sensor type: LED | Pitch reading angle: -65 - 65° | Power source type: Battery | Yaw reading angle: -45 - 45° | Depth: 76 mm | Wireless range: 100 m | Linear (1D) barcodes supported: Code 128 | Scanner type: 1D/2D | Storage temperature (T-T): -40 - 70 °C | 2D (matrix & stacked) barcodes supported: TLC-39 | 2D (matrix & stacked) barcodes supported: Composite Codes | Sustainability certificates: RoHS | Protection features: Shock resistant | Protection features: Dust resistant | Protection features: Water resistant | 2D (matrix & stacked) barcodes supported: PDF417 | Type: Handheld bar code reader | 2D (matrix & stacked) barcodes supported:

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjan rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

Han Xin | Number of reads per charge: 100000 | 2D (matrix & stacked) barcodes supported: QR Code | Linear (1D) barcodes supported: Code 11 | Linear (1D) barcodes supported: GS1-128 (UCC/EAN-128) | Linear (1D) barcodes supported: Plessey | 2D (matrix & stacked) barcodes supported: Data Matrix | 2D (matrix & stacked) barcodes supported: Micro QR Code | Optical sensor resolution: 1280 pixels | 2D (matrix & stacked) barcodes supported: MaxiCode | Bluetooth Low Energy (BLE): Yes | Linear (1D) barcodes supported: MSI | Linear (1D) barcodes supported: Code 93 | Linear (1D) barcodes supported: U.P.C. | Linear (1D) barcodes supported: Codabar | Connectivity technology: Wired & Wireless | Linear (1D) barcodes supported: Code 39 | 2D (matrix & stacked) barcodes supported: Aztec Code | 2D (matrix & stacked) barcodes supported: MicroPDF417