



Zebra DS9308-SR Fixed bar code reader 1D/2D LED Black



Modelis: DS9308-SR4U2100AZE

Gamintojas: ZEBRA

EAN:

Prekės kodas: 541716

135.99€

Certification: EN 50581:2012, RoHS 2011/65/EU (2015/863) - EN 50581:2012, IEC 63000, REACH 1907/2006, IEC 62368-1 2nd ed. EN 62368-1:2014/AC:2015, UL/IEC 60950-1, 2nd ed. CAN/CSA C22.2 No.60950-1, 2nd ed. IEC 62471:2006 (Ed.1.0), EN 62471:2008 (LED), FCC 47 CFR Part 15B, ICES-003, EN55032, EN55024, EN55035, VCCI, and SABS | Warnings: Store away from sources of moisture. | Warnings: The appliance should be disposed of in accordance with local electro-waste regulations. | Warnings: Avoid direct contact with eyes. | International Protection (IP) code: IP52 | Pitch reading angle: -60 - 60° | Optical sensor resolution (W x H): 1280 x 800 pixels | Operating relative humidity (H-H): 5 - 95% | Sensor type: LED | Weight: 318 g | Linear (1D) barcodes supported: GS1 DataBar | Linear (1D) barcodes supported: Code 11 | Linear (1D) barcodes supported: EAN-13 | Light levels (direct sunlight): 0 - 107700 lx | Working distance: 66 cm | Linear (1D) barcodes supported: Codabar | Operating temperature (T-T): 0 - 50 °C | Standard interfaces: RS-232, USB | Linear (1D) barcodes supported: Code 93 | Linear (1D) barcodes supported: U.P.C. | Linear (1D) barcodes supported: Code 39 | Height: 145 mm | Linear (1D) barcodes supported: MSI | Scanner type: 1D/2D | Connectivity technology: Wired | Product colour: Black | Linear (1D) barcodes supported: Code 128 | Storage

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

temperature (T-T): -40 - 70 °C | Depth: 83 mm | 2D (matrix & stacked) barcodes supported: MaxiCode | 2D (matrix & stacked) barcodes supported: PDF417 | 2D (matrix & stacked) barcodes supported: Aztec Code | 2D (matrix & stacked) barcodes supported: MicroPDF417 | 2D (matrix & stacked) barcodes supported: Dot Code A | 2D (matrix & stacked) barcodes supported: QR Code | 2D (matrix & stacked) barcodes supported: Han Xin | 2D (matrix & stacked) barcodes supported: Data Matrix | 2D (matrix & stacked) barcodes supported: TLC-39 | 2D (matrix & stacked) barcodes supported: Composite Codes | Type: Fixed bar code reader | 2D (matrix & stacked) barcodes supported: Micro QR Code | Harmonized System (HS) code: 84716070 | Width: 86 mm | Power source type: USB | Input voltage: 5.5 V | Power source type: RS-232