



Motorola LI4278 Black



Modelis: LI4278-TRBU0100ZER

Gamintojas: ZEBRA

Prekės kodas: 541719

210.99€

Decoding standards: UPC/EAN: UPC-A, UPC-E, UPC-E1, EAN-8/JAN 8, EAN-13/JAN 13, Bookland EAN, Bookland ISBN Format, UCC Coupon Extended Code, ISSN EAN Code 128 Including GS1-128, ISBT 128, ISBT Concatenation, Code 39 including Trioptic Code 39, Convert Code 39 to Code 32 (Italian Pharmacy Code), Code 39 Full ASCII Conversion Code 93 Code 11 Matrix 2 of 5 Interleaved 2 of 5 (ITF) Discrete 2 of 5 (DTF) Codabar (NW - 7) MSI Chinese 2 of 5 IATA Inverse 1D (except all GS1 DataBars) GS1 DataBar including GS1 DataBar-14, GS1 DataBar Limited, GS1 | Certification: EMC FCC Part 15 Class B, ICES 003 Class B, IEC 60601-1-2 RoHS 2002/95/EEC | Maximum scan width: 10 cm | Standard interfaces: RS-232, RS-485, USB, Keyboard wedge | Shockproof: No | Maximum range: 6 m | Weight: 224 g | Battery technology: Lithium Polymer (LiPo) | Operating temperature (T-T): 0 - 50 °C | Operating relative humidity (H-H): 5 - 85% | Read rate (max): 547 reads/s | Harmonized System (HS) code: 84716070 | International Protection (IP) code: IP54 | Storage temperature (T-T): - 40 - 70 °C | Product colour: Black | Dimensions (WxDxH): 70 x 186 x 98 mm | Tilt reading angle: 0 - 45° | Light source: LED | Light levels (direct sunlight): 0 - 108 lx | LED indicators: Power | Bluetooth: Yes | Cable length: 1.8 m | Wavelength: 612 nm | LED indicators: Charging | Yaw reading angle: 0 - 65° | Cables included: RS-232 | Safety: C22.2 No. 60950-1, EN 60950-1, IEC 60950-1, UL 60950- 1 LED Class 1 | Tilt angle range: 0 - 35° | Pitch reading angle: 0 - 65° | Housing material: Plastic

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903