Zebra DS2278 Rankinis brūkšninių kodų skaitytuvas 1D/2D LED Juoda

Gamintojas: **ZEBRA** · Modelis: **DS2278-SR7U2100PRW** · EAN: · Prekės kodas: **541840**



195,90 €

Kaina su PVM

Be PVM: **161,90 €**

Sandėlyje

Prekė internetu
Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Rankinis brūkšninių kodų skaitytuvas Juoda
- ✓ Skenerio tipas: 1D/2D Jutiklio tipas: LED
- ✓ Codabar, Code 11, Code 128, Code 39, Code 93, EAN-13, Interleaved 2 of 5, Plessey, U.P.C. Aztec Code, Sudėtiniai kodai, Duomenų matrica, Han Xin, MaxiCode, Micro QR Code, PDF417, QR Code, TLC-39
- ✓ 640 x 480 pikseliai
- ✓ Darbo atstumas: 36,8 cm
- ✓ Polinkio skaitymo kampas: -65 - 65°
- ✓ Vielinis ir Bevielis Standartinės sąsajos: „Bluetooth“, USB
- ✓ Nedaug energijos naudojantis „Bluetooth“ (BLE)
- ✓ Maitinimo šaltinio tipas: Baterija, DC Ličio-jonų (Li-Ion) 2400 mAh





Aprašymas

Affordability and Simplicity Delivered

2D barcodes have made their way to your Point of Sale, appearing on everything from the items your customers are purchasing to printed and electronic coupons and loyalty cards. Your 1D scanner can’t capture the new 2D codes, leading to exceptions that slow down the check-out process

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

and frustrate customers at that key last personal touchpoint in your store. But with the DS2200 Series, you can scan it all. You get an affordable 1D/2D imager that doesn't compromise performance or features for price. Your workers get best-in-class first-time, everytime scanning with point-and-shoot simplicity. You get an imager that couldn't be easier to deploy and manage. And you can choose the model that best fits your POS needs — the corded DS2208 or the cordless DS2278. The DS2200 Series — the affordability your budget demands, with the deployment, ease-of-use and management simplicity your business requires.

Easy to Deploy

Pre-configured and ready to use, right out of the box

Since the default settings are optimized for the majority of scanning applications, you can use the DS2200 Series imager the moment you take it out of the box — no configuration required.

Auto-host detect cables

Just plug the DS2200 Series into your Point of Sale (POS) and the auto-host detect cables will automatically identify the interface and connect the imager, simplifying and reducing setup time.

Easy integration with a tablet-based POS

The DS2200 Series offers all the features you need to add high-quality scanning to your tablet-based POS. The Micro USB cable provides a low-cost charging alternative to a cradle. And with our simplified app development tools, you can easily configure and update the DS2200 Series right from the tablet.

Deploy anywhere in the world

With over 90 international keyboards, the DS2200 Series is easy to deploy all around the world.

Easily customize settings with 123Scan

This complementary software tool is so intuitive that even a first time user can easily set up a DS2200 Series imager. The wizard-driven interface makes it easy to embed all settings into a single programming barcode, enabling you to configure your devices with a single scan.

Backwards compatible with Zebra LS2208 series cables

If you use Zebra's 1D LS2208 scanners today, you can use the same universal cables with the DS2200 Series, allowing you to leverage your existing accessory investment to minimize the cost of upgrading to a 1D/2D imager.

Easy to Use

Instant decoding with PRZM intelligent imaging

Only from Zebra, PRZM's software decode algorithms for the DS2200 Series deliver superior performance on poor quality barcodes. The result is first-time, every-time scanning to help your workers improve productivity at the checkout counter.

Unsurpassed scanning range

Workers can scan barcodes across a wide range (0.5 in./1.23 cm to 14.5 in./36.8 cm), improving checkout speed and reducing training time.

Point-and-shoot scanning simplicity

With omni-directional scanning, users never need to line up the imager and the barcode — unlike 1D scanners.

Patent pending technology for the most intuitive aiming

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

The aim line is similar to the 1D scanners you have today, providing your associates with a familiar experience. Additionally, the aim line guides users to scan at the ideal distance from the barcode — especially helpful when capturing wide barcodes.

Easiest pairing on the planet

With our industry-first Scan-to-Connect technology, your workers can pair the cordless DS2278 with any Bluetooth™-enabled PC, tablet or smartphone in a single step.

Fast, easy and flexible charging

Plug the imager directly into the host or any standard wall socket via the Micro USB cable to charge the DS2278 in just an hour without the cradle. The Presentation Cradle, which provides hands-free scanning, charges the DS2278 in just four hours. The Presentation Cradle charges the battery during use, so you can keep the scanner in service during charging. And since the Presentation Cradle doesn’t require a separate power supply, there are fewer accessories to purchase and manage.

Unique direct decode indicator improves productivity

The illumination on the barcode flashes to indicate a good decode, so workers know instantly if the barcode was captured correctly — regardless of how noisy the environment might be.

On-the-fly switching between handheld and hands-free scanning

Regardless of whether your workers are using the corded DS2208 or the cordless DS2278, workers can simply place the imager in its presentation stand to automatically switch to hands-free mode – no change of settings is required.

Guaranteed full shift battery power

With 14 hours of power, your cordless DS2278 imagers are always available for use — no need to waste time recharging during the business day.

Easy to Manage

Control your scanners from a smartphone, tablet or PC

You can easily control the beeper, LED and Symbology settings; display scanned barcode data; access model and serial number information and more from Windows®, Android™ and iOS® hosts.

Eliminate Bluetooth interference with Zebra’s proprietary Wi-Fi™ friendly mode

Ensure that your cordless DS2278 Bluetooth imagers only operate on channels that are not shared with your WLAN, protecting WLAN service levels for your workers and your customers.

A battery designed to last

The long-lasting 2400 mAh Lithium Ion battery in the cordless DS2278 will likely never need to be replaced, reducing total cost of ownership and simplifying everyday management by eliminating the need to purchase and manage a battery pool.

No-cost tools to meet advanced management and application development needs

If you have Imagers in different locations, you can remotely manage them all with our Scanner Management Service (SMS) application. Need a custom scanning application? Our Scanner Software Development Kits (SDKs) provide everything you need, including documentation, drivers, test utilities and sample source code for Windows, Android, iOS and Linux.

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

Techninė specifikacija

Nuskaitymas	
Tipas	Rankinis brūkšninių kodų skaitytuvas
Skenerio tipas	1D/2D
Jutiklio tipas	LED
Palaikomi linijiniai (1D) brūkšniniai kodai	Codabar, Code 11, Code 128, Code 39, Code 93, EAN-13, Interleaved 2 of 5, Plessey, U.P.C.
Palaikomi 2D (matricos ir sudėtiniai) brūkšniniai kodai	Aztec Code, Sudėtiniai kodai, Duomenų matrica, Han Xin, MaxiCode, Micro QR Code, PDF417, QR Code, TLC-39
Optinio jutiklio skiriamoji geba (plotis x aukštis)	640 x 480 pikseliai
Darbo atstumas	36,8 cm
Bangos ilgis	645 nm
Polinkio skaitymo kampas	-65 - 65°
Pitch skaitymo kampas	-65 - 65°
Judesių tolerancija (cm/s)	13
Ryšys	
Ryšio technologija	Vielinis ir Bevielis
Standartinės sąsajos	„Bluetooth“, USB
Bluetooth versija	4.0
Nedaug energijos naudojantis „Bluetooth“ (BLE)	Taip
Veikimo charakteristikos	
Produkto spalva	Juoda
Tarptautinės apsaugos (IP) kodas	IP42
LED indikatoriai	Taip
Įmontuotas ekranas	Ne
Sertifikavimas	EN 60950-1 2ed + A11 + A1 + A12 + A2:2013, IEC 60950-1 2ed + A1 + A2, UL 60950-1, CAN/CSA-C22.2 No. 60950- 1-07
Energijos valdymas	
Maitinimo šaltinio tipas	Baterija, DC
Palaikomų baterijų skaičius	1
Baterijos veikimo trukmė	84 h
Įėjimo įtampa	4.5 - 5.5 V
Svoris ir matmenys	
Svoris	214 g
Plotis	66 mm

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

Ilgis	90 mm
Aukštis	175 mm
Pakuotės duomenys	
Kroviklio bazė	Taip
Aplinkos sąlygos	
Darbo temperatūros diapazonas (TT)	0 - 50 °C
Sandėliavimo temperatūros norma (T-T)	-40 - 70 °C
Darbo santykinės drėgmės diapazonas	5 - 95%
Baterija	
Baterijos technologija	Ličio-jonų (Li-Ion)
Baterijos talpa	2400 mAh
Techninė informacija	
Atitikties sertifikatai	RoHS
Logistikos duomenys	
Darniosios sistemos (DS) kodas	84716070
Matmenys ir svoris	
Matmenys (I × P × A)	22,00cm × 15,00cm × 18,00cm
Svoris	0,74kg

Dokumentai ir vaizdo įrašai

- Naudojimo instrukcija
- Gaminio lankstinukas
- Vaizdo įrašas objects.icecat.biz/objects/mmo-37989020-14307066.html

Gamintojo ir saugos informacija

GAMINTOJAS

Zebra

ATSAKINGAS ASMUO ES

Zebra Technologies
Borupvang 3, Ballerup, DK
zebra.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU
V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.