



TP-Link 8-Port Gigabit Desktop PoE Switch with 4-Port



Modelis: TL-SG1008P

Gamintojas: TP-LINK

EAN: 1210002616690

Prekės kodas: 541943

51.99€

Certification: CE, FCC, RoHS | Virtual LAN features: IP subnet-based VLAN | Depth: 98 mm | Rack mounting: No | Harmonized System (HS) code: 85176990 | Power over Ethernet (PoE): Yes | Width: 171 mm | LED indicators: Error | DHCP features: DHCPv6 client | MAC address table: 4800 entries | Routing protocols: IP | Store-and-forward: Yes | Auto MDI/MDI-X: Yes | Package type: Box | Operating temperature (T-T): 0 - 40 °C | Switch type: Unmanaged | Copper ethernet cabling technology: 100BASE-T | Ethernet LAN data rates: 1000 | Gigabit Ethernet (copper) ports quantity: 8 | Fiber ethernet cabling technology: 40GBASE-LR4 | Height: 27 mm | Full duplex: Yes | Basic switching RJ-45 Ethernet ports quantity: 8 | Power over Ethernet (PoE) type supported: Active PoE | Input current: 1.25 A | Compatible memory cards: MMC Mobile | IPv4 & IPv6 features: IPv6 Telnet | Power connector: DC-in jack | DC input voltage: 48 V | Authentication: Auto VLAN | Operating relative humidity (H-H): 10 - 90% | User guide: Yes | Flow control support: Yes | Queue scheduling algorithms: SP | Power over Ethernet (PoE) ports quantity: 4 | Storage temperature (T-T): -40 - 70 °C | Authentication type: HWTACACS | VLAN mapping type: 2:2 VLAN Mapping | 10G support: No | Power supply included: Yes | Cables included: AC | Switching capacity: 16 Gbit/s | Power consumption

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

(typical): 53 W | Networking standards: IEEE 802.11j | Storage relative humidity (H-H): 5 - 90% | Security algorithms: HTTPS | Housing material: Polymer | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Fiber optic connector: LuxCis | Number of power supply units: 1 | MAC address entries: Blackhole MAC address entries | Cable types supported: Cat6a | Sustainability certificates: ENERGY STAR | Airflow direction: Back-to-front airflow | Product colour: Hazelnut